

The utrace User Debugging Infrastructure

The utrace User Debugging Infrastructure

Table of Contents

1. utrace concepts	1
1.1. Introduction	1
1.2. Events and Callbacks	1
1.3. Stopping Safely	2
1.3.1. Writing well-behaved callbacks	2
1.3.2. Using <code>UTRACE_STOP</code>	2
1.4. Tear-down Races	3
1.4.1. Primacy of <code>SIGKILL</code>	3
1.4.2. Final callbacks	3
1.4.3. Engine and task pointers	4
1.4.4. Serialization of <code>DEATH</code> and <code>REAP</code>	4
1.4.5. Interlock with final callbacks	5
1.4.6. Using <code>utrace_barrier</code>	6
2. utrace core API	7
enum <code>utrace_resume_action</code>	7
<code>utrace_resume_action</code>	8
enum <code>utrace_signal_action</code>	9
<code>utrace_signal_action</code>	10
enum <code>utrace_syscall_action</code>	11
<code>utrace_syscall_action</code>	12
struct <code>utrace_attached_engine</code>	13
<code>utrace_engine_get</code>	14
<code>utrace_engine_put</code>	15
struct <code>utrace_engine_ops</code>	16
struct <code>utrace_examiner</code>	21
<code>utrace_control_pid</code>	21
<code>utrace_set_events_pid</code>	22
<code>utrace_barrier_pid</code>	23
<code>utrace_attach_task</code>	24
<code>utrace_attach_pid</code>	26
<code>utrace_set_events</code>	27
<code>utrace_control</code>	28
<code>utrace_barrier</code>	32
<code>utrace_prepare_examine</code>	33
<code>utrace_finish_examine</code>	34
3. Machine State	37
3.1. struct <code>user_regset</code>	37
<code>user_regset_active_fn</code>	37
<code>user_regset_get_fn</code>	38
<code>user_regset_set_fn</code>	39

user_regset_writeback_fn	41
struct user_regset	42
struct user_regset_view	44
task_user_regset_view	45
copy_regset_to_user	46
copy_regset_from_user	47
3.2. System Call Information	48
task_current_syscall	49
3.3. System Call Tracing	50
syscall_get_nr	50
syscall_rollback	51
syscall_get_error	52
syscall_get_return_value	53
syscall_set_return_value	54
syscall_get_arguments	55
syscall_set_arguments	57
4. Kernel Internals	59
4.1. Core Calls In	59
tracehook_expect_breakpoints	59
tracehook_report_syscall_entry	60
tracehook_report_syscall_exit	61
tracehook_unsafe_exec	62
tracehook_tracer_task	63
tracehook_report_exec	64
tracehook_report_exit	65
tracehook_prepare_clone	65
tracehook_finish_clone	66
tracehook_report_clone	67
tracehook_report_clone_complete	69
tracehook_report_vfork_done	70
tracehook_prepare_release_task	71
tracehook_finish_release_task	72
tracehook_signal_handler	73
tracehook_consider_ignored_signal	74
tracehook_consider_fatal_signal	75
tracehook_force_sigpending	76
tracehook_get_signal	77
tracehook_notify_jctl	78
tracehook_notify_death	79
tracehook_report_death	80
set_notify_resume	82
tracehook_notify_resume	82
4.2. Architecture Calls Out	83

4.2.1. <asm/ptrace.h>	83
arch_has_single_step	84
arch_has_block_step	84
user_enable_single_step	85
user_enable_block_step	86
user_disable_single_step.....	87
4.2.2. <asm/syscall.h>	88
4.2.3. <linux/tracehook.h>	88

Chapter 1. utrace concepts

1.1. Introduction

utrace is infrastructure code for tracing and controlling user threads. This is the foundation for writing tracing engines, which can be loadable kernel modules.

The basic actors in utrace are the thread and the tracing engine. A tracing engine is some body of code that calls into the `<linux/utrace.h>` interfaces, represented by a struct `utrace_engine_ops`. (Usually it's a kernel module, though the legacy `ptrace` support is a tracing engine that is not in a kernel module.) The interface operates on individual threads (struct `task_struct`). If an engine wants to treat several threads as a group, that is up to its higher-level code.

Tracing begins by attaching an engine to a thread, using `utrace_attach_task` or `utrace_attach_pid`. If successful, it returns a pointer that is the handle used in all other calls.

1.2. Events and Callbacks

An attached engine does nothing by default. An engine makes something happen by requesting callbacks via `utrace_set_events` and poking the thread with `utrace_control`. The synchronization issues related to these two calls are discussed further below in Section 1.4.

Events are specified using the macro `UTRACE_EVENT(type)`. Each event type is associated with a callback in struct `utrace_engine_ops`. A tracing engine can leave unused callbacks `NULL`. The only callbacks required are those used by the event flags it sets.

Many engines can be attached to each thread. When a thread has an event, each engine gets a callback if it has set the event flag for that event type. Engines are called in the order they attached.

Event reporting callbacks have details particular to the event type, but are all called in similar environments and have the same constraints. Callbacks are made from safe points, where no locks are held, no special resources are pinned (usually), and the user-mode state of the thread is accessible. So, callback code has a pretty free hand. But to be a good citizen, callback code should never block for long periods. It is fine to block in `kmalloc` and the like, but never wait for i/o or for user mode to do something. If you need the thread to wait, use `UTRACE_STOP` and return from the

callback quickly. When your i/o finishes or whatever, you can use `utrace_control` to resume the thread.

1.3. Stopping Safely

1.3.1. Writing well-behaved callbacks

Well-behaved callbacks are important to maintain two essential properties of the interface. The first of these is that unrelated tracing engines should not interfere with each other. If your engine's event callback does not return quickly, then another engine won't get the event notification in a timely manner. The second important property is that tracing should be as noninvasive as possible to the normal operation of the system overall and of the traced thread in particular. That is, attached tracing engines should not perturb a thread's behavior, except to the extent that changing its user-visible state is explicitly what you want to do. (Obviously some perturbation is unavoidable, primarily timing changes, ranging from small delays due to the overhead of tracing, to arbitrary pauses in user code execution when a user stops a thread with a debugger for examination.) Even when you explicitly want the perturbation of making the traced thread block, just blocking directly in your callback has more unwanted effects. For example, the `CLONE` event callbacks are called when the new child thread has been created but not yet started running; the child can never be scheduled until the `CLONE` tracing callbacks return. (This allows engines tracing the parent to attach to the child.) If a `CLONE` event callback blocks the parent thread, it also prevents the child thread from running (even to process a `SIGKILL`). If what you want is to make both the parent and child block, then use `utrace_attach_task` on the child and then use `UTRACE_STOP` on both threads. A more crucial problem with blocking in callbacks is that it can prevent `SIGKILL` from working. A thread that is blocking due to `UTRACE_STOP` will still wake up and die immediately when sent a `SIGKILL`, as all threads should. Relying on the utrace infrastructure rather than on private synchronization calls in event callbacks is an important way to help keep tracing robustly noninvasive.

1.3.2. Using `UTRACE_STOP`

To control another thread and access its state, it must be stopped with `UTRACE_STOP`. This means that it is stopped and won't start running again while we access it. When a thread is not already stopped, `utrace_control` returns `-EINPROGRESS` and an engine must wait for an event callback when the thread is ready to stop. The thread may be running on another CPU or may be blocked. When it is ready to be examined, it will make callbacks to engines that set the

`UTRACE_EVENT(QUIESCE)` event bit. To wake up an interruptible wait, use `UTRACE_INTERRUPT`.

As long as some engine has used `UTRACE_STOP` and not called `utrace_control` to resume the thread, then the thread will remain stopped. `SIGKILL` will wake it up, but it will not run user code. When the stop is cleared with `utrace_control` or a callback return value, the thread starts running again. (See also Section 1.4.)

1.4. Tear-down Races

1.4.1. Primacy of `SIGKILL`

Ordinarily synchronization issues for tracing engines are kept fairly straightforward by using `UTRACE_STOP`. You ask a thread to stop, and then once it makes the `report_quiesce` callback it cannot do anything else that would result in another callback, until you let it with a `utrace_control` call. This simple arrangement avoids complex and error-prone code in each one of a tracing engine's event callbacks to keep them serialized with the engine's other operations done on that thread from another thread of control. However, giving tracing engines complete power to keep a traced thread stuck in place runs afoul of a more important kind of simplicity that the kernel overall guarantees: nothing can prevent or delay `SIGKILL` from making a thread die and release its resources. To preserve this important property of `SIGKILL`, it as a special case can break `UTRACE_STOP` like nothing else normally can. This includes both explicit `SIGKILL` signals and the implicit `SIGKILL` sent to each other thread in the same thread group by a thread doing an `exec`, or processing a fatal signal, or making an `exit_group` system call. A tracing engine can prevent a thread from beginning the `exit` or `exec` or dying by signal (other than `SIGKILL`) if it is attached to that thread, but once the operation begins, no tracing engine can prevent or delay all other threads in the same thread group dying.

1.4.2. Final callbacks

The `report_reap` callback is always the final event in the life cycle of a traced thread. Tracing engines can use this as the trigger to clean up their own data structures. The `report_death` callback is always the penultimate event a tracing engine might see; it's seen unless the thread was already in the midst of dying when the engine attached. Many tracing engines will have no interest in when a parent reaps a dead process, and nothing they want to do with a zombie thread once it dies; for them, the `report_death` callback is the natural place to clean up data

structures and detach. To facilitate writing such engines robustly, given the asynchrony of `SIGKILL`, and without error-prone manual implementation of synchronization schemes, the utrace infrastructure provides some special guarantees about the `report_death` and `report_reap` callbacks. It still takes some care to be sure your tracing engine is robust to tear-down races, but these rules make it reasonably straightforward and concise to handle a lot of corner cases correctly.

1.4.3. Engine and task pointers

The first sort of guarantee concerns the core data structures themselves. `struct utrace_attached_engine` is a reference-counted data structure. While you hold a reference, an engine pointer will always stay valid so that you can safely pass it to any utrace call. Each call to `utrace_attach_task` or `utrace_attach_pid` returns an engine pointer with a reference belonging to the caller. You own that reference until you drop it using `utrace_engine_put`. There is an implicit reference on the engine while it is attached. So if you drop your only reference, and then use `utrace_attach_task` without `UTRACE_ATTACH_CREATE` to look up that same engine, you will get the same pointer with a new reference to replace the one you dropped, just like calling `utrace_engine_get`. When an engine has been detached, either explicitly with `UTRACE_DETACH` or implicitly after `report_reap`, then any references you hold are all that keep the old engine pointer alive.

There is nothing a kernel module can do to keep a `struct task_struct` alive outside of `rcu_read_lock`. When the task dies and is reaped by its parent (or itself), that structure can be freed so that any dangling pointers you have stored become invalid. utrace will not prevent this, but it can help you detect it safely. By definition, a task that has been reaped has had all its engines detached. All utrace calls can be safely called on a detached engine if the caller holds a reference on that engine pointer, even if the task pointer passed in the call is invalid. All calls return `-ESRCH` for a detached engine, which tells you that the task pointer you passed could be invalid now. Since `utrace_control` and `utrace_set_events` do not block, you can call those inside a `rcu_read_lock` section and be sure after they don't return `-ESRCH` that the task pointer is still valid until `rcu_read_unlock`. The infrastructure never holds task references of its own. Though neither `rcu_read_lock` nor any other lock is held while making a callback, it's always guaranteed that the `struct task_struct` and the `struct utrace_attached_engine` passed as arguments remain valid until the callback function returns.

The common means for safely holding task pointers that is available to kernel modules is to use `struct pid`, which permits `put_pid` from kernel modules. When using that, the calls `utrace_attach_pid`, `utrace_control_pid`, `utrace_set_events_pid`, and `utrace_barrier_pid` are available.

1.4.4. Serialization of DEATH and REAP

The second guarantee is the serialization of `DEATH` and `REAP` event callbacks for a given thread. The actual reaping by the parent (`release_task` call) can occur simultaneously while the thread is still doing the final steps of dying, including the `report_death` callback. If a tracing engine has requested both `DEATH` and `REAP` event reports, it's guaranteed that the `report_reap` callback will not be made until after the `report_death` callback has returned. If the `report_death` callback itself detaches from the thread, then the `report_reap` callback will never be made. Thus it is safe for a `report_death` callback to clean up data structures and detach.

1.4.5. Interlock with final callbacks

The final sort of guarantee is that a tracing engine will know for sure whether or not the `report_death` and/or `report_reap` callbacks will be made for a certain thread. These tear-down races are disambiguated by the error return values of `utrace_set_events` and `utrace_control`. Normally `utrace_control` called with `UTRACE_DETACH` returns zero, and this means that no more callbacks will be made. If the thread is in the midst of dying, it returns `-EALREADY` to indicate that the `report_death` callback may already be in progress; when you get this error, you know that any cleanup your `report_death` callback does is about to happen or has just happened--note that if the `report_death` callback does not detach, the engine remains attached until the thread gets reaped. If the thread is in the midst of being reaped, `utrace_control` returns `-ESRCH` to indicate that the `report_reap` callback may already be in progress; this means the engine is implicitly detached when the callback completes. This makes it possible for a tracing engine that has decided asynchronously to detach from a thread to safely clean up its data structures, knowing that no `report_death` or `report_reap` callback will try to do the same. `utrace_detach` returns `-ESRCH` when the struct `utrace_attached_engine` has already been detached, but is still a valid pointer because of its reference count. A tracing engine can use this to safely synchronize its own independent multiple threads of control with each other and with its event callbacks that detach.

In the same vein, `utrace_set_events` normally returns zero; if the target thread was stopped before the call, then after a successful call, no event callbacks not requested in the new flags will be made. It fails with `-EALREADY` if you try to clear `UTRACE_EVENT(DEATH)` when the `report_death` callback may already have begun, if you try to clear `UTRACE_EVENT(REAP)` when the `report_reap` callback may already have begun, or if you try to newly set `UTRACE_EVENT(DEATH)` or `UTRACE_EVENT(QUIESCE)` when the target is already dead or dying. Like `utrace_control`, it returns `-ESRCH` when the thread has already been detached (including forcible detach on reaping). This lets the tracing engine know for sure

which event callbacks it will or won't see after `utrace_set_events` has returned. By checking for errors, it can know whether to clean up its data structures immediately or to let its callbacks do the work.

1.4.6. Using `utrace_barrier`

When a thread is safely stopped, calling `utrace_control` with `UTRACE_DETACH` or calling `utrace_set_events` to disable some events ensures synchronously that your engine won't get any more of the callbacks that have been disabled (none at all when detaching). But these can also be used while the thread is not stopped, when it might be simultaneously making a callback to your engine. For this situation, these calls return `-EINPROGRESS` when it's possible a callback is in progress. If you are not prepared to have your old callbacks still run, then you can synchronize to be sure all the old callbacks are finished, using `utrace_barrier`. This is necessary if the kernel module containing your callback code is going to be unloaded.

After using `UTRACE_DETACH` once, further calls to `utrace_control` with the same engine pointer will return `-ESRCH`. In contrast, after getting `-EINPROGRESS` from `utrace_set_events`, you can call `utrace_set_events` again later and if it returns zero then know the old callbacks have finished.

Unlike all other calls, `utrace_barrier` (and `utrace_barrier_pid`) will accept any engine pointer you hold a reference on, even if `UTRACE_DETACH` has already been used. After any `utrace_control` or `utrace_set_events` call (these do not block), you can call `utrace_barrier` to block until callbacks have finished. This returns `-ESRCH` only if the engine is completely detached (finished all callbacks). Otherwise returns it waits until the thread is definitely not in the midst of a callback to this engine and then returns zero, but can return `-ERESTARTSYS` if its wait is interrupted.

Chapter 2. utrace core API

The utrace API is declared in `<linux/utrace.h>`.

enum utrace_resume_action

LINUX

Kernel Hackers Manual February 2009

Name

enum utrace_resume_action — engine's choice of action for a traced task

Synopsis

```
enum utrace_resume_action {
    UTRACE_STOP,
    UTRACE_REPORT,
    UTRACE_INTERRUPT,
    UTRACE_SINGLESTEP,
    UTRACE_BLOCKSTEP,
    UTRACE_RESUME,
    UTRACE_DETACH
};
```

Constants

UTRACE_STOP

Stay quiescent after callbacks.

UTRACE_REPORT

Make some callback soon.

UTRACE_INTERRUPT

Make *report_signal()* callback soon.

UTRACE_SINGLESTEP

Resume in user mode for one instruction.

UTRACE_BLOCKSTEP

Resume in user mode until next branch.

UTRACE_RESUME

Resume normally in user mode.

UTRACE_DETACH

Detach my engine (implies UTRACE_RESUME).

Description

See `utrace_control` for detailed descriptions of each action. This is encoded in the *action* argument and the return value for every callback with a u32 return value.

The order of these is important. When there is more than one engine, each supplies its choice and the smallest value prevails.

utrace_resume_action

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_resume_action` — enum `utrace_resume_action` from callback action

Synopsis

```
enum utrace_resume_action utrace_resume_action (u32 action);
```

Arguments

action

u32 callback *action* argument or return value

Description

This extracts the enum `utrace_resume_action` from *action*, which is the *action* argument to a struct `utrace_engine_ops` callback or the return value from one.

enum utrace_signal_action

LINUX

Kernel Hackers Manual February 2009

Name

enum `utrace_signal_action` — disposition of signal

Synopsis

```
enum utrace_signal_action {
    UTRACE_SIGNAL_DELIVER,
    UTRACE_SIGNAL_IGN,
    UTRACE_SIGNAL_TERM,
    UTRACE_SIGNAL_CORE,
    UTRACE_SIGNAL_STOP,
    UTRACE_SIGNAL_TSTP,
    UTRACE_SIGNAL_REPORT,
    UTRACE_SIGNAL_HANDLER
};
```

Constants

UTRACE_SIGNAL_DELIVER

Deliver according to sigaction.

UTRACE_SIGNAL_IGN

Ignore the signal.

UTRACE_SIGNAL_TERM

Terminate the process.

UTRACE_SIGNAL_CORE

Terminate with core dump.

UTRACE_SIGNAL_STOP

Deliver as absolute stop.

UTRACE_SIGNAL_TSTP

Deliver as job control stop.

UTRACE_SIGNAL_REPORT

Reporting before pending signals.

UTRACE_SIGNAL_HANDLER

Reporting after signal handler setup.

Description

This is encoded in the *action* argument and the return value for a *report_signal()* callback. It says what will happen to the signal described by the *siginfo_t* parameter to the callback.

The UTRACE_SIGNAL_REPORT value is used in an *action* argument when a tracing report is being made before dequeuing any pending signal. If this is immediately after a signal handler has been set up, then

UTRACE_SIGNAL_HANDLER is used instead. A *report_signal* callback that uses UTRACE_SIGNAL_DELIVER|UTRACE_SINGLESTEP will ensure it sees a UTRACE_SIGNAL_HANDLER report.

utrace_signal_action

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_signal_action` — enum `utrace_signal_action` from callback action

Synopsis

```
enum utrace_signal_action utrace_signal_action (u32 action);
```

Arguments

action

report_signal callback *action* argument or return value

Description

This extracts the enum `utrace_signal_action` from *action*, which is the *action* argument to a *report_signal* callback or the return value from one.

enum utrace_syscall_action

LINUX

Name

`enum utrace_syscall_action` — disposition of system call attempt

Synopsis

```
enum utrace_syscall_action {
    UTRACE_SYSCALL_RUN,
    UTRACE_SYSCALL_ABORT
};
```

Constants

`UTRACE_SYSCALL_RUN`

Run the system call.

`UTRACE_SYSCALL_ABORT`

Don't run the system call.

Description

This is encoded in the *action* argument and the return value for a *report_syscall_entry* callback.

utrace_syscall_action

LINUX

Name

`utrace_syscall_action` — enum `utrace_syscall_action` from callback action

Synopsis

```
enum utrace_syscall_action utrace_syscall_action (u32 action);
```

Arguments

action

report_syscall_entry callback *action* or return value

Description

This extracts the enum `utrace_syscall_action` from *action*, which is the *action* argument to a *report_syscall_entry* callback or the return value from one.

struct utrace_attached_engine

LINUX

Kernel Hackers Manual February 2009

Name

`struct utrace_attached_engine` — per-engine structure

Synopsis

```
struct utrace_attached_engine {
    const struct utrace_engine_ops * ops;
    void * data;
    unsigned long flags;
};
```

Members

`ops`

struct `utrace_engine_ops` pointer passed to `utrace_attach_task`

`data`

engine-private void * passed to `utrace_attach_task`

`flags`

event mask set by `utrace_set_events` plus internal flag bits

Description

The task itself never has to worry about engines detaching while it's doing event callbacks. These structures are removed from the task's active list only when it's stopped, or by the task itself.

`utrace_engine_get` and `utrace_engine_put` maintain a reference count. When it drops to zero, the structure is freed. One reference is held implicitly while the engine is attached to its task.

`utrace_engine_get`

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_engine_get` — acquire a reference on a struct `utrace_attached_engine`

Synopsis

```
void utrace_engine_get (struct utrace_attached_engine *  
engine);
```

Arguments

engine

struct `utrace_attached_engine` pointer

Description

You must hold a reference on *engine*, and you get another.

utrace_engine_put

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_engine_put` — release a reference on a struct `utrace_attached_engine`

Synopsis

```
void utrace_engine_put (struct utrace_attached_engine *  
engine);
```

Arguments

engine

struct `utrace_attached_engine` pointer

Description

You must hold a reference on *engine*, and you lose that reference. If it was the last one, *engine* becomes an invalid pointer.

struct utrace_engine_ops

LINUX

Kernel Hackers Manual February 2009

Name

struct utrace_engine_ops — tracing engine callbacks

Synopsis

```
struct utrace_engine_ops {
    u32 (* report_quiesce) (enum utrace_resume_action action, struct utrace_
    u32 (* report_signal) (u32 action, struct utrace_attached_engine *engine,
    u32 (* report_clone) (enum utrace_resume_action action, struct utrace_at
    u32 (* report_jctl) (enum utrace_resume_action action, struct utrace_atta
    u32 (* report_exec) (enum utrace_resume_action action, struct utrace_atta
    u32 (* report_syscall_entry) (u32 action, struct utrace_attached_engine *
    u32 (* report_syscall_exit) (enum utrace_resume_action action, struct utr
    u32 (* report_exit) (enum utrace_resume_action action, struct utrace_atta
    u32 (* report_death) (struct utrace_attached_engine *engine, struct task_
    void (* report_reap) (struct utrace_attached_engine *engine, struct task_
    int (* unsafe_exec) (struct utrace_attached_engine *engine, struct task_
    struct task_struct *(* tracer_task) (struct utrace_attached_engine *eng
};
```

Members

report_quiesce

Requested by `UTRACE_EVENT(QUIESCE)`. This does not indicate any event, but just that *task* (the current thread) is in a safe place for examination. This

call is made before each specific event callback, except for *report_reap*. The *event* argument gives the `UTRACE_EVENT(which)` value for the event occurring. This callback might be made for events *engine* has not requested, if some other engine is tracing the event; calling `utrace_set_events` call here can request the immediate callback for this occurrence of *event*. *event* is zero when there is no other event, *task* is now ready to check for signals and return to user mode, and some engine has used `UTRACE_REPORT` or `UTRACE_INTERRUPT` to request this callback. For this case, if *report_signal* is not `NULL`, the *report_quiesce* callback may be replaced with a *report_signal* callback passing `UTRACE_SIGNAL_REPORT` in its *action* argument, whenever *task* is entering the signal-check path anyway.

report_signal

Requested by `UTRACE_EVENT(SIGNAL_*)` or `UTRACE_EVENT(QUIESCE)`. Use `utrace_signal_action` and `utrace_resume_action` on *action*. The signal action is `UTRACE_SIGNAL_REPORT` when some engine has used `UTRACE_REPORT` or `UTRACE_INTERRUPT`; the callback can choose to stop or to deliver an artificial signal, before pending signals. It's `UTRACE_SIGNAL_HANDLER` instead when signal handler setup just finished (after a previous `UTRACE_SIGNAL_DELIVER` return); this serves in lieu of any `UTRACE_SIGNAL_REPORT` callback requested by `UTRACE_REPORT` or `UTRACE_INTERRUPT`, and is also implicitly requested by `UTRACE_SINGLESTEP` or `UTRACE_BLOCKSTEP` into the signal delivery. The other signal actions indicate a signal about to be delivered; the previous engine's return value sets the signal action seen by the the following engine's callback. The *info* data can be changed at will, including *info->si_signo*. The settings in *return_ka* determines what `UTRACE_SIGNAL_DELIVER` does. *orig_ka* is what was in force before other tracing engines intervened, and it's `NULL` when this report began as `UTRACE_SIGNAL_REPORT` or `UTRACE_SIGNAL_HANDLER`. For a report without a new signal, *info* is left uninitialized and must be set completely by an engine that chooses to deliver a signal; if there was a previous *report_signal* callback ending in `UTRACE_STOP` and it was just resumed using `UTRACE_REPORT` or `UTRACE_INTERRUPT`, then *info* is left unchanged from the previous callback. In this way, the original signal can be left in *info* while returning `UTRACE_STOP|UTRACE_SIGNAL_IGN` and then found again when resuming *task* with `UTRACE_INTERRUPT`. The `UTRACE_SIGNAL_HOLD` flag bit can be OR'd into the return value, and might be in *action* if the previous engine returned it. This flag asks that the signal in *info* be pushed back on *task*'s queue so that it will be seen again after whatever action is taken now.

report_clone

Requested by `UTRACE_EVENT(CLONE)`. Event reported for parent, before the

new task *child* might run. *clone_flags* gives the flags used in the clone system call, or equivalent flags for a *fork* or *vfork* system call. This function can use *utrace_attach_task* on *child*. It's guaranteed that asynchronous *utrace_attach_task* calls will be ordered after any calls in *report_clone* callbacks for the parent. Thus when using *UTRACE_ATTACH_EXCLUSIVE* in the asynchronous calls, you can be sure that the parent's *report_clone* callback has already attached to *child* or chosen not to. Passing *UTRACE_STOP* to *utrace_control* on *child* here keeps the child stopped before it ever runs in user mode, *UTRACE_REPORT* or *UTRACE_INTERRUPT* ensures a callback from *child* before it starts in user mode.

report_jctl

Requested by *UTRACE_EVENT(JCTL)*. Job control event; *type* is *CLD_STOPPED* or *CLD_CONTINUED*, indicating whether we are stopping or resuming now. If *notify* is nonzero, *task* is the last thread to stop and so will send *SIGCHLD* to its parent after this callback; *notify* reflects what the parent's *SIGCHLD* has in *si_code*, which can sometimes be *CLD_STOPPED* even when *type* is *CLD_CONTINUED*.

report_exec

Requested by *UTRACE_EVENT(EXEC)*. An *execve* system call has succeeded and the new program is about to start running. The initial user register state is handy to be tweaked directly in *regs*. *fmt* and *bprm* gives the details of this exec.

report_syscall_entry

Requested by *UTRACE_EVENT(SYSCALL_ENTRY)*. Thread has entered the kernel to request a system call. The user register state is handy to be tweaked directly in *regs*. The *action* argument contains an enum *utrace_syscall_action*, use *utrace_syscall_action* to extract it. The return value overrides the last engine's action for the system call. If the final action is *UTRACE_SYSCALL_ABORT*, no system call is made. The details of the system call being attempted can be fetched here with *syscall_get_nr* and *syscall_get_arguments*. The parameter registers can be changed with *syscall_set_arguments*.

report_syscall_exit

Requested by *UTRACE_EVENT(SYSCALL_EXIT)*. Thread is about to leave the kernel after a system call request. The user register state is handy to be tweaked directly in *regs*. The results of the system call attempt can be examined here using *syscall_get_error* and *syscall_get_return_value*. It is safe here to call *syscall_set_return_value* or *syscall_rollback*.

report_exit

Requested by `UTRACE_EVENT(EXIT)`. Thread is exiting and cannot be prevented from doing so, but all its state is still live. The `code` value will be the wait result seen by the parent, and can be changed by this engine or others. The `orig_code` value is the real status, not changed by any tracing engine.

Returning `UTRACE_STOP` here keeps `task` stopped before it cleans up its state and dies, so it can be examined by other processes. When `task` is allowed to run, it will die and get to the `report_death` callback.

report_death

Requested by `UTRACE_EVENT(DEATH)`. Thread is really dead now. It might be reaped by its parent at any time, or self-reap immediately. Though the actual reaping may happen in parallel, a `report_reap` callback will always be ordered after a `report_death` callback.

report_reap

Requested by `UTRACE_EVENT(REAP)`. Called when someone reaps the dead task (parent, init, or self). This means the parent called wait, or else this was a detached thread or a process whose parent ignores `SIGCHLD`. No more callbacks are made after this one. The engine is always detached. There is nothing more a tracing engine can do about this thread. After this callback, the `engine` pointer will become invalid. The `task` pointer may become invalid if `get_task_struct` hasn't been used to keep it alive. An engine should always request this callback if it stores the `engine` pointer or stores any pointer in `engine->data`, so it can clean up its data structures. Unlike other callbacks, this can be called from the parent's context rather than from the traced thread itself--it must not delay the parent by blocking.

unsafe_exec

Used if not `NULL`. Return `LSM_UNSAFE_*` bits that apply to the exec in progress due to tracing done by this engine. These bits indicate that someone is able to examine the process and so a set-UID or similar privilege escalation may not be safe to permit. Called with `task_lock` held.

tracer_task

Used if not `NULL`. Return the struct `task_struct` for the task using `ptrace` on `task`, or `NULL`. Always called with `rcu_read_lock` held to keep the returned struct alive. At exec time, this may be called with `task_lock` still held from when `unsafe_exec` was just called. In that case it must give results consistent with those `unsafe_exec` results, i.e. non-`NULL` if any `LSM_UNSAFE_PTRACE_*` bits were set. The value is also used to display after

“TracerPid:” in /proc/PID/status, where it is called with only `rcu_read_lock` held. If this engine returns `NULL`, another engine may supply the result.

Description

Each `report_*`() callback corresponds to an `UTRACE_EVENT(*)` bit.

`utrace_set_events` calls on `engine` choose which callbacks will be made to `engine` from `task`.

Most callbacks take an `action` argument, giving the resume action chosen by other tracing engines. All callbacks take an `engine` argument, and a `task` argument, which is always equal to `current`. For some calls, `action` also includes bits specific to that event and `utrace_resume_action` is used to extract the resume action. This shows what would happen if `engine` wasn't there, or will if the callback's return value uses `UTRACE_RESUME`. This always starts as `UTRACE_RESUME` when no other tracing is being done on this task.

All return values contain enum `utrace_resume_action` bits. For some calls, other bits specific to that kind of event are added to the resume action bits with OR. These are the same bits used in the `action` argument. The resume action returned by a callback does not override previous engines' choices, it only says what `engine` wants done. What `task` actually does is the action that's most constrained among the choices made by all attached engines. See `utrace_control` for more information on the actions.

When `UTRACE_STOP` is used in `report_syscall_entry`, then `task` stops before attempting the system call. In other cases, the resume action does not take effect until `task` is ready to check for signals and return to user mode. If there are more callbacks to be made, the last round of calls determines the final action. A `report_quiesce` callback with `event` zero, or a `report_signal` callback, will always be the last one made before `task` resumes. Only `UTRACE_STOP` is “sticky”—if `engine` returned `UTRACE_STOP` then `task` stays stopped unless `engine` returns different from a following callback.

The `report_death` and `report_reap` callbacks do not take `action` arguments, and only `UTRACE_DETACH` is meaningful in the return value from a `report_death` callback. None of the resume actions applies to a dead thread.

All `report_*`() hooks are called with no locks held, in a generally safe environment when we will be returning to user mode soon (or just entered the kernel). It is fine to block for memory allocation and the like, but all hooks are asynchronous and must not block on external events! If you want the thread to block, use `UTRACE_STOP` in your hook's return value; then later wake it up with `utrace_control`.

The *unsafe_exec* and *tracer_task* hooks are not associated with event reports. These may be `NULL` if the engine has nothing to say. These hooks are called in more constrained environments and should not block or do very much.

struct *utrace_examiner*

LINUX

Kernel Hackers Manual February 2009

Name

`struct utrace_examiner` — private state for using `utrace_prepare_examine`

Synopsis

```
struct utrace_examiner {  
    struct dummy;  
};
```

Members

`dummy`

all fields are private, none described here

Description

The members of `struct utrace_examiner` are private to the implementation. This data type holds the state from a call to `utrace_prepare_examine` to be used by a call to `utrace_finish_examine`.

utrace_control_pid

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_control_pid` — control a thread being traced by a tracing engine

Synopsis

```
__must_check int utrace_control_pid (struct pid * pid, struct
utrace_attached_engine * engine, enum utrace_resume_action
action);
```

Arguments

pid

thread to affect

engine

attached engine to affect

action

enum `utrace_resume_action` for thread to do

Description

This is the same as `utrace_control`, but takes a struct `pid` pointer rather than a struct `task_struct` pointer. The caller must hold a ref on *pid*, but does not need to worry about the task staying valid. If it's been reaped so that *pid* points nowhere, then this call returns `-ESRCH`.

utrace_set_events_pid

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_set_events_pid` — choose which event reports a tracing engine gets

Synopsis

```
__must_check int utrace_set_events_pid (struct pid * pid,
struct utrace_attached_engine * engine, unsigned long
eventmask);
```

Arguments

pid

thread to affect

engine

attached engine to affect

eventmask

new event mask

Description

This is the same as `utrace_set_events`, but takes a struct pid pointer rather than a struct task_struct pointer. The caller must hold a ref on *pid*, but does not need to worry about the task staying valid. If it's been reaped so that *pid* points nowhere, then this call returns `-ESRCH`.

utrace_barrier_pid

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_barrier_pid` — synchronize with simultaneous tracing callbacks

Synopsis

```
__must_check int utrace_barrier_pid (struct pid * pid, struct
utrace_attached_engine * engine);
```

Arguments

pid

thread to affect

engine

engine to affect (can be detached)

Description

This is the same as `utrace_barrier`, but takes a struct pid pointer rather than a struct task_struct pointer. The caller must hold a ref on *pid*, but does not need to worry about the task staying valid. If it's been reaped so that *pid* points nowhere, then this call returns `-ESRCH`.

utrace_attach_task

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_attach_task` — attach new engine, or look up an attached engine

Synopsis

```
struct utrace_attached_engine * utrace_attach_task (struct
task_struct * target, int flags, const struct
utrace_engine_ops * ops, void * data);
```

Arguments

target

thread to attach to

flags

flag bits combined with OR, see below

ops

callback table for new engine

data

engine private data pointer

Description

The caller must ensure that the *target* thread does not get freed, i.e. hold a ref or be its parent. It is always safe to call this on *current*, or on the *child* pointer in a *report_clone* callback. For most other cases, it's easier to use `utrace_attach_pid` instead.

UTRACE_ATTACH_CREATE

Create a new engine. If `UTRACE_ATTACH_CREATE` is not specified, you only look up an existing engine already attached to the thread.

UTRACE_ATTACH_EXCLUSIVE

Attempting to attach a second (matching) engine fails with `-EEXIST`.

UTRACE_ATTACH_MATCH_OPS

Only consider engines matching *ops*.

UTRACE_ATTACH_MATCH_DATA

Only consider engines matching *data*.

utrace_attach_pid

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_attach_pid` — attach new engine, or look up an attached engine

Synopsis

```
struct utrace_attached_engine * utrace_attach_pid (struct pid
* pid, int flags, const struct utrace_engine_ops * ops, void *
data);
```


Arguments

pid

struct pid pointer representing thread to attach to

flags

flag bits combined with OR, see `utrace_attach_task`

ops

callback table for new engine

data

engine private data pointer

Description

This is the same as `utrace_attach_task`, but takes a struct pid pointer rather than a struct task_struct pointer. The caller must hold a ref on *pid*, but does not need to worry about the task staying valid. If it's been reaped so that *pid* points nowhere, then this call returns `-ESRCH`.

utrace_set_events

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_set_events` — choose which event reports a tracing engine gets

Synopsis

```
int utrace_set_events (struct task_struct * target, struct
utrace_attached_engine * engine, unsigned long events);
```

Arguments

target

thread to affect

engine

attached engine to affect

events

new event mask

Description

This changes the set of events for which *engine* wants callbacks made.

This fails with `-EALREADY` and does nothing if you try to clear `UTRACE_EVENT(DEATH)` when the *report_death* callback may already have begun, if you try to clear `UTRACE_EVENT(REAP)` when the *report_reap* callback may already have begun, or if you try to newly set `UTRACE_EVENT(DEATH)` or `UTRACE_EVENT(QUIESCE)` when *target* is already dead or dying.

This can fail with `-ESRCH` when *target* has already been detached, including forcible detach on reaping.

If *target* was stopped before the call, then after a successful call, no event callbacks not requested in *events* will be made; if `UTRACE_EVENT(QUIESCE)` is included in *events*, then a *report_quiesce* callback will be made when *target* resumes. If *target* was not stopped, and was about to make a callback to *engine*, this returns `-EINPROGRESS`. In this case, the callback in progress might be one excluded from the new *events* setting. When this returns zero, you can be sure that no event callbacks you've disabled in *events* can be made.

To synchronize after an `-EINPROGRESS` return, see `utrace_barrier`.

These rules provide for coherent synchronization based on `UTRACE_STOP`, even when `SIGKILL` is breaking its normal simple rules.

utrace_control

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_control` — control a thread being traced by a tracing engine

Synopsis

```
int utrace_control (struct task_struct * target, struct
utrace_attached_engine * engine, enum utrace_resume_action
action);
```

Arguments

target

thread to affect

engine

attached engine to affect

action

enum `utrace_resume_action` for thread to do

Description

This is how a tracing engine asks a traced thread to do something. This call is controlled by the *action* argument, which has the same meaning as the enum `utrace_resume_action` value returned by event reporting callbacks.

If *target* is already dead (*target*->`exit_state` nonzero), all actions except `UTRACE_DETACH` fail with `-ESRCH`.

The following sections describe each option for the *action* argument.

UTRACE_DETACH

After this, the *engine* data structure is no longer accessible, and the thread might be reaped. The thread will start running again if it was stopped and no longer has any attached engines that want it stopped.

If the *report_reap* callback may already have begun, this fails with `-ESRCH`. If the *report_death* callback may already have begun, this fails with `-EALREADY`.

If *target* is not already stopped, then a callback to this engine might be in progress or about to start on another CPU. If so, then this returns `-EINPROGRESS`; the detach happens as soon as the pending callback is finished. To synchronize after an `-EINPROGRESS` return, see *utrace_barrier*.

If *target* is properly stopped before *utrace_control* is called, then after successful return it's guaranteed that no more callbacks to the *engine->ops* vector will be made.

The only exception is `SIGKILL` (and `exec` or `group-exit` by another thread in the group), which can cause asynchronous *report_death* and/or *report_reap* callbacks even when `UTRACE_STOP` was used. (In that event, this fails with `-ESRCH` or `-EALREADY`, see above.)

UTRACE_STOP

This asks that *target* stop running. This returns 0 only if *target* is already stopped, either for tracing or for job control. Then *target* will remain stopped until another *utrace_control* call is made on *engine*; *target* can be woken only by `SIGKILL` (or equivalent, such as `exec` or termination by another thread in the same thread group).

This returns `-EINPROGRESS` if *target* is not already stopped. Then the effect is like `UTRACE_REPORT`. A *report_quiesce* or *report_signal* callback will be made soon. Your callback can then return `UTRACE_STOP` to keep *target* stopped.

This does not interrupt system calls in progress, including ones that sleep for a long time. For that, use `UTRACE_INTERRUPT`. To interrupt system calls and then keep *target* stopped, your *report_signal* callback can return `UTRACE_STOP`.

UTRACE_RESUME

Just let *target* continue running normally, reversing the effect of a previous `UTRACE_STOP`. If another engine is keeping *target* stopped, then it remains stopped until all engines let it resume. If *target* was not stopped, this has no effect.

UTRACE_REPORT

This is like `UTRACE_RESUME`, but also ensures that there will be a `report_quiesce` or `report_signal` callback made soon. If *target* had been stopped, then there will be a callback before it resumes running normally. If another engine is keeping *target* stopped, then there might be no callbacks until all engines let it resume.

UTRACE_INTERRUPT

This is like `UTRACE_REPORT`, but ensures that *target* will make a `report_signal` callback before it resumes or delivers signals. If *target* was in a system call or about to enter one, work in progress will be interrupted as if by `SIGSTOP`. If another engine is keeping *target* stopped, then there might be no callbacks until all engines let it resume.

This gives *engine* an opportunity to introduce a forced signal disposition via its `report_signal` callback.

UTRACE_SINGLESTEP

It's invalid to use this unless `arch_has_single_step` returned true. This is like `UTRACE_RESUME`, but resumes for one user instruction only. It's invalid to use this in `utrace_control` unless *target* had been stopped by *engine* previously.

Note that passing `UTRACE_SINGLESTEP` or `UTRACE_BLOCKSTEP` to `utrace_control` or returning it from an event callback alone does not necessarily ensure that stepping will be enabled. If there are more callbacks made to any engine before returning to user mode, then the resume action is chosen only by the last set of callbacks. To be sure, enable `UTRACE_EVENT(QUIESCE)` and look for the `report_quiesce` callback with a zero event mask, or the `report_signal` callback with `UTRACE_SIGNAL_REPORT`.

UTRACE_BLOCKSTEP

It's invalid to use this unless `arch_has_block_step` returned true. This is like `UTRACE_SINGLESTEP`, but resumes for one whole basic block of user instructions.

`UTRACE_BLOCKSTEP` devolves to `UTRACE_SINGLESTEP` when another tracing engine is using `UTRACE_SINGLESTEP` at the same time.

utrace_barrier

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_barrier` — synchronize with simultaneous tracing callbacks

Synopsis

```
int utrace_barrier (struct task_struct * target, struct
utrace_attached_engine * engine);
```

Arguments

target

thread to affect

engine

engine to affect (can be detached)

Description

This blocks while *target* might be in the midst of making a callback to *engine*. It can be interrupted by signals and will return `-ERESTARTSYS`. A return value of zero means no callback from *target* to *engine* was in progress.

It's not necessary to keep the *target* pointer alive for this call. It's only necessary to hold a ref on *engine*. This will return safely even if *target* has been reaped and has no task refs.

A successful return from `utrace_barrier` guarantees its ordering with respect to `utrace_set_events` and `utrace_control` calls. If *target* was not properly stopped, event callbacks just disabled might still be in progress; `utrace_barrier` waits until there is no chance an unwanted callback can be in progress.

utrace_prepare_examine

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_prepare_examine` — prepare to examine thread state

Synopsis

```
int utrace_prepare_examine (struct task_struct * target,
struct utrace_attached_engine * engine, struct utrace_examiner
* exam);
```

Arguments

target

thread of interest, a struct `task_struct` pointer

engine

engine pointer returned by `utrace_attach_task`

exam

temporary state, a struct `utrace_examiner` pointer

Description

This call prepares to safely examine the thread *target* using struct `user_regset` calls, or direct access to thread-synchronous fields.

When *target* is current, this call is superfluous. When *target* is another thread, it must held stopped via `UTRACE_STOP` by *engine*.

This call may block the caller until *target* stays stopped, so it must be called only after the caller is sure *target* is about to unschedule. This means a zero return from a `utrace_control` call on *engine* giving `UTRACE_STOP`, or a `report_quiesce` or `report_signal` callback to *engine* that used `UTRACE_STOP` in its return value.

Returns `-ESRCH` if *target* is dead or `-EINVAL` if `UTRACE_STOP` was not used. If *target* has started running again despite `UTRACE_STOP` (for `SIGKILL` or a spurious wakeup), this call returns `-EAGAIN`.

When this call returns zero, it's safe to use struct `user_regset` calls and `task_user_regset_view` on *target* and to examine some of its fields directly. When the examination is complete, a `utrace_finish_examine` call must follow to check whether it was completed safely.

utrace_finish_examine

LINUX

Kernel Hackers Manual February 2009

Name

`utrace_finish_examine` — complete an examination of thread state

Synopsis

```
int utrace_finish_examine (struct task_struct * target, struct
utrace_attached_engine * engine, struct utrace_examiner *
exam);
```


Arguments

target

thread of interest, a struct `task_struct` pointer

engine

engine pointer returned by `utrace_attach_task`

exam

pointer passed to `utrace_prepare_examine` call

Description

This call completes an examination on the thread *target* begun by a paired `utrace_prepare_examine` call with the same arguments that returned success (zero).

When *target* is current, this call is superfluous. When *target* is another thread, this returns zero if *target* has remained unscheduled since the paired `utrace_prepare_examine` call returned zero.

When this returns an error, any examination done since the paired `utrace_prepare_examine` call is unreliable and the data extracted should be discarded. The error is `-EINVAL` if *engine* is not keeping *target* stopped, or `-EAGAIN` if *target* woke up unexpectedly.

Chapter 3. Machine State

The `task_current_syscall` function can be used on any valid struct `task_struct` at any time, and does not even require that `utrace_attach_task` was used at all.

The other ways to access the registers and other machine-dependent state of a task can only be used on a task that is at a known safe point. The safe points are all the places where `utrace_set_events` can request callbacks (except for the `DEATH` and `REAP` events). So at any event callback, it is safe to examine `current`.

One task can examine another only after a callback in the target task that returns `UTRACE_STOP` so that task will not return to user mode after the safe point. This guarantees that the task will not resume until the same engine uses `utrace_control`, unless the task dies suddenly. To examine safely, one must use a pair of calls to `utrace_prepare_examine` and `utrace_finish_examine` surrounding the calls to struct `user_regset` functions or direct examination of task data structures. `utrace_prepare_examine` returns an error if the task is not properly stopped and not dead. After a successful examination, the paired `utrace_finish_examine` call returns an error if the task ever woke up during the examination. If so, any data gathered may be scrambled and should be discarded. This means there was a spurious wake-up (which should not happen), or a sudden death.

3.1. struct user_regset

The struct `user_regset` API is declared in `<linux/regset.h>`.

user_regset_active_fn

LINUX

Kernel Hackers Manual February 2009

Name

`user_regset_active_fn` — type of *active* function in struct `user_regset`

Synopsis

```
typedef int user_regset_active_fn (struct task_struct *  
target, const struct user_regset * regset);
```

Arguments

target

thread being examined

regset

regset being examined

Description

Return `-ENODEV` if not available on the hardware found. Return 0 if no interesting state in this thread. Return `>0` number of *size* units of interesting state. Any get call fetching state beyond that number will see the default initialization state for this data, so a caller that knows what the default state is need not copy it all out. This call is optional; the pointer is `NULL` if there is no inexpensive check to yield a value `< n`.

user_regset_get_fn

LINUX

Kernel Hackers Manual February 2009

Name

`user_regset_get_fn` — type of *get* function in struct `user_regset`

Synopsis

```
typedef int user_regset_get_fn (struct task_struct * target,  
const struct user_regset * regset, unsigned int pos, unsigned  
int count, void * kbuf, void __user * ubuf);
```

Arguments

target

thread being examined

regset

regset being examined

pos

offset into the regset data to access, in bytes

count

amount of data to copy, in bytes

kbuf

if not NULL, a kernel-space pointer to copy into

ubuf

if *kbuf* is NULL, a user-space pointer to copy into

Description

Fetch register values. Return 0 on success; -EIO or -ENODEV are usual failure returns. The *pos* and *count* values are in bytes, but must be properly aligned. If *kbuf* is non-null, that buffer is used and *ubuf* is ignored. If *kbuf* is NULL, then *ubuf* gives a userland pointer to access directly, and an -EFAULT return value is possible.

user_regset_set_fn

LINUX

Kernel Hackers Manual February 2009

Name

`user_regset_set_fn` — type of *set* function in struct `user_regset`

Synopsis

```
typedef int user_regset_set_fn (struct task_struct * target,  
const struct user_regset * regset, unsigned int pos, unsigned  
int count, const void * kbuf, const void __user * ubuf);
```

Arguments

target

thread being examined

regset

regset being examined

pos

offset into the regset data to access, in bytes

count

amount of data to copy, in bytes

kbuf

if not NULL, a kernel-space pointer to copy from

ubuf

if *kbuf* is NULL, a user-space pointer to copy from

Description

Store register values. Return 0 on success; -EIO or -ENODEV are usual failure returns. The *pos* and *count* values are in bytes, but must be properly aligned. If *kbuf* is non-null, that buffer is used and *ubuf* is ignored. If *kbuf* is NULL, then *ubuf* gives a userland pointer to access directly, and an -EFAULT return value is possible.

user_regset_writeback_fn

LINUX

Kernel Hackers Manual February 2009

Name

`user_regset_writeback_fn` — type of *writeback* function in struct `user_regset`

Synopsis

```
typedef int user_regset_writeback_fn (struct task_struct *
target, const struct user_regset * regset, int immediate);
```

Arguments

target

thread being examined

regset

regset being examined

immediate

zero if writeback at completion of next context switch is OK

Description

This call is optional; usually the pointer is `NULL`. When provided, there is some user memory associated with this `regset`'s hardware, such as memory backing cached register data on register window machines; the `regset`'s data controls what user memory is used (e.g. via the stack pointer value).

Write register data back to user memory. If the *immediate* flag is nonzero, it must be written to the user memory so `uaccess` or `access_process_vm` can see it when this call returns; if zero, then it must be written back by the time the task completes a context switch (as synchronized with `wait_task_inactive`). Return 0 on success or if there was nothing to do, `-EFAULT` for a memory problem (bad stack pointer or whatever), or `-EIO` for a hardware problem.

struct user_regset

LINUX

Kernel Hackers Manual February 2009

Name

`struct user_regset` — accessible thread CPU state

Synopsis

```
struct user_regset {
    user_regset_get_fn * get;
    user_regset_set_fn * set;
    user_regset_active_fn * active;
    user_regset_writeback_fn * writeback;
    unsigned int n;
    unsigned int size;
    unsigned int align;
    unsigned int bias;
    unsigned int core_note_type;
};
```


Members

`get`

Function to fetch values.

`set`

Function to store values.

`active`

Function to report if regset is active, or `NULL`.

`writeback`

Function to write data back to user memory, or `NULL`.

`n`

Number of slots (registers).

`size`

Size in bytes of a slot (register).

`align`

Required alignment, in bytes.

`bias`

Bias from natural indexing.

`core_note_type`

ELF note *n_type* value used in core dumps.

Description

This data structure describes a machine resource we call a register set. This is part of the state of an individual thread, not necessarily actual CPU registers per se. A register set consists of a number of similar slots, given by *n*. Each slot is *size* bytes, and aligned to *align* bytes (which is at least *size*).

These functions must be called only on the current thread or on a thread that is in `TASK_STOPPED` or `TASK_TRACED` state, that we are guaranteed will not be woken up and return to user mode, and that we have called `wait_task_inactive` on. (The target thread always might wake up for `SIGKILL` while these functions are working, in which case that thread's `user_regset` state might be scrambled.)

The *pos* argument must be aligned according to *align*; the *count* argument must be a multiple of *size*. These functions are not responsible for checking for invalid arguments.

When there is a natural value to use as an index, *bias* gives the difference between the natural index and the slot index for the register set. For example, x86 GDT segment descriptors form a regset; the segment selector produces a natural index, but only a subset of that index space is available as a regset (the TLS slots); subtracting *bias* from a segment selector index value computes the regset slot.

If nonzero, *core_note_type* gives the *n_type* field (NT_* value) of the core file note in which this regset's data appears. NT_PRSTATUS is a special case in that the regset data starts at `offsetof(struct elf_prstatus, pr_reg)` into the note data; that is part of the per-machine ELF formats userland knows about. In other cases, the core file note contains exactly the whole regset ($n * size$) and nothing else. The core file note is normally omitted when there is an *active* function and it returns zero.

struct user_regset_view

LINUX

Kernel Hackers Manual February 2009

Name

struct user_regset_view — available regsets

Synopsis

```
struct user_regset_view {
    const char * name;
    const struct user_regset * regsets;
    unsigned int n;
    u32 e_flags;
    u16 e_machine;
    u8 ei_osabi;
};
```

Members

`name`

Identifier, e.g. UTS_MACHINE string.

`regsets`

Array of n regsets available in this view.

`n`

Number of elements in `regsets`.

`e_flags`

ELF header `e_flags` value written in core dumps.

`e_machine`

ELF header `e_machine` EM_* value written in core dumps.

`ei_osabi`

ELF header `e_ident[EI_OSABI]` value written in core dumps.

Description

A regset view is a collection of regsets (struct `user_regset`, above). This describes all the state of a thread that can be seen from a given architecture/ABI environment. More than one view might refer to the same struct `user_regset`, or more than one regset might refer to the same machine-specific state in the thread. For example, a 32-bit thread's state could be examined from the 32-bit view or from the 64-bit view. Either method reaches the same thread register state, doing appropriate widening or truncation.

task_user_regset_view

LINUX

Name

`task_user_regset_view` — Return the process's native regset view.

Synopsis

```
const struct user_regset_view * task_user_regset_view (struct
task_struct * tsk);
```

Arguments

tsk

a thread of the process in question

Description

Return the struct `user_regset_view` that is native for the given process. For example, what it would access when it called `ptrace`. Throughout the life of the process, this only changes at `exec`.

copy_regset_to_user

LINUX

Name

`copy_regset_to_user` — fetch a thread's `user_regset` data into user memory

Synopsis

```
int copy_regset_to_user (struct task_struct * target, const
struct user_regset_view * view, unsigned int setno, unsigned
int offset, unsigned int size, void __user * data);
```

Arguments

target

thread to be examined

view

struct user_regset_view describing user thread machine state

setno

index in *view->regsets*

offset

offset into the regset data, in bytes

size

amount of data to copy, in bytes

data

user-mode pointer to copy into

copy_regset_from_user

LINUX

Name

`copy_regset_from_user` — store into thread's `user_regset` data from user memory

Synopsis

```
int copy_regset_from_user (struct task_struct * target, const
struct user_regset_view * view, unsigned int setno, unsigned
int offset, unsigned int size, const void __user * data);
```

Arguments

target

thread to be examined

view

struct `user_regset_view` describing user thread machine state

setno

index in `view->regsets`

offset

offset into the regset data, in bytes

size

amount of data to copy, in bytes

data

user-mode pointer to copy from

3.2. System Call Information

This function is declared in `<linux/ptrace.h>`.

task_current_syscall

LINUX

Kernel Hackers Manual February 2009

Name

`task_current_syscall` — Discover what a blocked task is doing.

Synopsis

```
int task_current_syscall (struct task_struct * target, long *  
callno, unsigned long args[6], unsigned int maxargs, unsigned  
long * sp, unsigned long * pc);
```

Arguments

target

thread to examine

callno

filled with system call number or -1

args[6]

filled with *maxargs* system call arguments

maxargs

number of elements in *args* to fill

sp

filled with user stack pointer

pc

filled with user PC

Description

If *target* is blocked in a system call, returns zero with **callno* set to the the call's number and *args* filled in with its arguments. Registers not used for system call arguments may not be available and it is not kosher to use struct *user_regset* calls while the system call is still in progress. Note we may get this result if *target* has finished its system call but not yet returned to user mode, such as when it's stopped for signal handling or syscall exit tracing.

If *target* is blocked in the kernel during a fault or exception, returns zero with **callno* set to -1 and does not fill in *args*. If so, it's now safe to examine *target* using struct *user_regset* get calls as long as we're sure *target* won't return to user mode.

Returns -EAGAIN if *target* does not remain blocked.

Returns -EINVAL if *maxargs* is too large (maximum is six).

3.3. System Call Tracing

The arch API for system call information is declared in `<asm/syscall.h>`. Each of these calls can be used only at system call entry tracing, or can be used only at system call exit and the subsequent safe points before returning to user mode. At system call entry tracing means either during a *report_syscall_entry* callback, or any time after that callback has returned `UTRACE_STOP`.

syscall_get_nr

LINUX

Kernel Hackers Manual February 2009

Name

`syscall_get_nr` — find what system call a task is executing

Synopsis

```
long syscall_get_nr (struct task_struct * task, struct pt_regs
* regs);
```

Arguments

task

task of interest, must be blocked

regs

task_pt_regs of *task*

Description

If *task* is executing a system call or is at system call tracing about to attempt one, returns the system call number. If *task* is not executing a system call, i.e. it's blocked inside the kernel for a fault or signal, returns -1.

It's only valid to call this when *task* is known to be blocked.

syscall_rollback

LINUX

Kernel Hackers Manual February 2009

Name

`syscall_rollback` — roll back registers after an aborted system call

Synopsis

```
void syscall_rollback (struct task_struct * task, struct  
pt_regs * regs);
```

Arguments

task

task of interest, must be in system call exit tracing

regs

task_pt_regs of *task*

Description

It's only valid to call this when *task* is stopped for system call exit tracing (due to TIF_SYSCALL_TRACE or TIF_SYSCALL_AUDIT), after `tracehook_report_syscall_entry` returned nonzero to prevent the system call from taking place.

This rolls back the register state in *regs* so it's as if the system call instruction was a no-op. The registers containing the system call number and arguments are as they were before the system call instruction. This may not be the same as what the register state looked like at system call entry tracing.

syscall_get_error

LINUX

Kernel Hackers Manual February 2009

Name

`syscall_get_error` — check result of traced system call

Synopsis

```
long syscall_get_error (struct task_struct * task, struct
pt_regs * regs);
```

Arguments

task

task of interest, must be blocked

regs

task_pt_regs of *task*

Description

Returns 0 if the system call succeeded, or -ERRORCODE if it failed.

It's only valid to call this when *task* is stopped for tracing on exit from a system call, due to TIF_SYSCALL_TRACE or TIF_SYSCALL_AUDIT.

syscall_get_return_value

LINUX

Kernel Hackers Manual February 2009

Name

syscall_get_return_value — get the return value of a traced system call

Synopsis

```
long syscall_get_return_value (struct task_struct * task,  
struct pt_regs * regs);
```

Arguments

task

task of interest, must be blocked

regs

task_pt_regs of *task*

Description

Returns the return value of the successful system call. This value is meaningless if `syscall_get_error` returned nonzero.

It's only valid to call this when *task* is stopped for tracing on exit from a system call, due to `TIF_SYSCALL_TRACE` or `TIF_SYSCALL_AUDIT`.

syscall_set_return_value

LINUX

Kernel Hackers Manual February 2009

Name

`syscall_set_return_value` — change the return value of a traced system call

Synopsis

```
void syscall_set_return_value (struct task_struct * task,
struct pt_regs * regs, int error, long val);
```

Arguments

task

task of interest, must be blocked

regs

task_pt_regs of *task*

error

negative error code, or zero to indicate success

val

user return value if *error* is zero

Description

This changes the results of the system call that user mode will see. If *error* is zero, the user sees a successful system call with a return value of *val*. If *error* is nonzero, it's a negated errno code; the user sees a failed system call with this errno code.

It's only valid to call this when *task* is stopped for tracing on exit from a system call, due to TIF_SYSCALL_TRACE or TIF_SYSCALL_AUDIT.

syscall_get_arguments

LINUX

Name

`syscall_get_arguments` — extract system call parameter values

Synopsis

```
void syscall_get_arguments (struct task_struct * task, struct  
pt_regs * regs, unsigned int i, unsigned int n, unsigned long  
* args);
```

Arguments

task

task of interest, must be blocked

regs

`task_pt_regs` of *task*

i

argument index [0,5]

n

number of arguments; $n+i$ must be [1,6].

args

array filled with argument values

Description

Fetches *n* arguments to the system call starting with the *i*'th argument (from 0 through 5). Argument *i* is stored in `args[0]`, and so on. An arch inline version is probably optimal when *i* and *n* are constants.

It's only valid to call this when *task* is stopped for tracing on entry to a system call, due to `TIF_SYSCALL_TRACE` or `TIF_SYSCALL_AUDIT`. It's invalid to call this with $i + n > 6$; we only support system calls taking up to 6 arguments.

syscall_set_arguments

LINUX

Kernel Hackers Manual February 2009

Name

`syscall_set_arguments` — change system call parameter value

Synopsis

```
void syscall_set_arguments (struct task_struct * task, struct
pt_regs * regs, unsigned int i, unsigned int n, const unsigned
long * args);
```

Arguments

task

task of interest, must be in system call entry tracing

regs

`task_pt_regs` of *task*

i

argument index [0,5]

n

number of arguments; $n+i$ must be [1,6].

args

array of argument values to store

Description

Changes n arguments to the system call starting with the i 'th argument. Argument i gets value *args*[0], and so on. An arch inline version is probably optimal when i and n are constants.

It's only valid to call this when *task* is stopped for tracing on entry to a system call, due to TIF_SYSCALL_TRACE or TIF_SYSCALL_AUDIT. It's invalid to call this with $i + n > 6$; we only support system calls taking up to 6 arguments.

Chapter 4. Kernel Internals

This chapter covers the interface to the tracing infrastructure from the core of the kernel and the architecture-specific code. This is for maintainers of the kernel and arch code, and not relevant to using the tracing facilities described in preceding chapters.

4.1. Core Calls In

These calls are declared in `<linux/tracehook.h>`. The core kernel calls these functions at various important places.

tracehook_expect_breakpoints

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_expect_breakpoints` — guess if task memory might be touched

Synopsis

```
int tracehook_expect_breakpoints (struct task_struct * task);
```

Arguments

task

current task, making a new mapping

Description

Return nonzero if *task* is expected to want breakpoint insertion in its memory at some point. A zero return is no guarantee it won't be done, but this is a hint that it's known to be likely.

May be called with *task*->mm->mmap_sem held for writing.

tracehook_report_syscall_entry

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_report_syscall_entry` — task is about to attempt a system call

Synopsis

```
__must_check int tracehook_report_syscall_entry (struct  
pt_regs * regs);
```

Arguments

regs

user register state of current task

Description

This will be called if `TIF_SYSCALL_TRACE` has been set, when the current task has just entered the kernel for a system call. Full user register state is available here.

Changing the values in *regs* can affect the system call number and arguments to be tried. It is safe to block here, preventing the system call from beginning.

Returns zero normally, or nonzero if the calling arch code should abort the system call. That must prevent normal entry so no system call is made. If *task* ever returns to user mode after this, its register state is unspecified, but should be something harmless like an `ENOSYS` error return. It should preserve enough information so that `syscall_rollback` can work (see `asm-generic/syscall.h`).

Called without locks, just after entering kernel mode.

tracehook_report_syscall_exit

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_report_syscall_exit` — task has just finished a system call

Synopsis

```
void tracehook_report_syscall_exit (struct pt_regs * regs, int
step);
```

Arguments

regs

user register state of current task

step

nonzero if simulating single-step or block-step

Description

This will be called if `TIF_SYSCALL_TRACE` has been set, when the current task has just finished an attempted system call. Full user register state is available here. It is safe to block here, preventing signals from being processed.

If *step* is nonzero, this report is also in lieu of the normal trap that would follow the system call instruction because `user_enable_block_step` or `user_enable_single_step` was used. In this case, `TIF_SYSCALL_TRACE` might not be set.

Called without locks, just before checking for pending signals.

tracehook_unsafe_exec

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_unsafe_exec` — check for exec declared unsafe due to tracing

Synopsis

```
int tracehook_unsafe_exec (struct task_struct * task);
```

Arguments

task

current task doing exec

Description

Return `LSM_UNSAFE_*` bits applied to an exec because of tracing.

Called with `task_lock` held on *task*.

tracehook_tracer_task

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_tracer_task` — return the task that is tracing the given task

Synopsis

```
struct task_struct * tracehook_tracer_task (struct task_struct
* tsk);
```

Arguments

tsk

task to consider

Description

Returns NULL if noone is tracing *task*, or the struct `task_struct` pointer to its tracer.

Must called under `rcu_read_lock`. The pointer returned might be kept live only by RCU. During exec, this may be called with `task_lock` held on *task*, still held from when `tracehook_unsafe_exec` was called.

tracehook_report_exec

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_report_exec` — a successful exec was completed

Synopsis

```
void tracehook_report_exec (struct linux_binfmt * fmt, struct  
linux_binprm * bprm, struct pt_regs * regs);
```

Arguments

fmt

struct linux_binfmt that performed the exec

bprm

struct linux_binprm containing exec details

regs

user-mode register state

Description

An exec just completed, we are shortly going to return to user mode. The freshly initialized register state can be seen and changed in *regs*. The name, file and other pointers in *bprm* are still on hand to be inspected, but will be freed as soon as this returns.

Called with no locks, but with some kernel resources held live and a reference on *fmt->module*.

tracehook_report_exit

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_report_exit` — task has begun to exit

Synopsis

```
void tracehook_report_exit (long * exit_code);
```

Arguments

exit_code

pointer to value destined for *current->exit_code*

Description

exit_code points to the value passed to `do_exit`, which tracing might change here. This is almost the first thing in `do_exit`, before freeing any resources or setting the `PF_EXITING` flag.

Called with no locks held.

tracehook_prepare_clone

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_prepare_clone` — prepare for new child to be cloned

Synopsis

```
int tracehook_prepare_clone (unsigned clone_flags);
```

Arguments

clone_flags

CLONE_* flags from clone/fork/vfork system call

Description

This is called before a new user task is to be cloned. Its return value will be passed to `tracehook_finish_clone`.

Called with no locks held.

tracehook_finish_clone

LINUX

Name

`tracehook_finish_clone` — new child created and being attached

Synopsis

```
void tracehook_finish_clone (struct task_struct * child,  
unsigned long clone_flags, int trace);
```

Arguments

child

new child task

clone_flags

CLONE_* flags from clone/fork/vfork system call

trace

return value from `tracehook_prepare_clone`

Description

This is called immediately after adding *child* to its parent's children list. The *trace* value is that returned by `tracehook_prepare_clone`.

Called with current's siglock and `write_lock_irq(tasklist_lock)` held.

tracehook_report_clone

LINUX

Name

`tracehook_report_clone` — in parent, new child is about to start running

Synopsis

```
void tracehook_report_clone (int trace, struct pt_regs * regs,  
unsigned long clone_flags, pid_t pid, struct task_struct *  
child);
```

Arguments

trace

return value from `tracehook_prepare_clone`

regs

parent's user register state

clone_flags

flags from parent's system call

pid

new child's PID in the parent's namespace

child

new child task

Description

Called after a child is set up, but before it has been started running. *trace* is the value returned by `tracehook_prepare_clone`. This is not a good place to block, because the child has not started yet. Suspend the child here if desired, and then block in `tracehook_report_clone_complete`. This must prevent the child from self-reaping if `tracehook_report_clone_complete` uses the *child*

pointer; otherwise it might have died and been released by the time `tracehook_report_clone_complete` is called.

Called with no locks held, but the child cannot run until this returns.

tracehook_report_clone_complete

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_report_clone_complete` — new child is running

Synopsis

```
void tracehook_report_clone_complete (int trace, struct
pt_regs * regs, unsigned long clone_flags, pid_t pid, struct
task_struct * child);
```

Arguments

trace

return value from `tracehook_prepare_clone`

regs

parent's user register state

clone_flags

flags from parent's system call

pid

new child's PID in the parent's namespace

child

child task, already running

Description

This is called just after the child has started running. This is just before the clone/fork syscall returns, or blocks for vfork child completion if *clone_flags* has the CLONE_VFORK bit set. The *child* pointer may be invalid if a self-reaping child died and `tracehook_report_clone` took no action to prevent it from self-reaping.

Called with no locks held.

tracehook_report_vfork_done

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_report_vfork_done` — vfork parent's child has exited or exec'd

Synopsis

```
void tracehook_report_vfork_done (struct task_struct * child,  
pid_t pid);
```

Arguments

child

child task, already running

pid

new child's PID in the parent's namespace

Description

Called after a `CLONE_VFORK` parent has waited for the child to complete. The clone/vfork system call will return immediately after this. The *child* pointer may be invalid if a self-reaping child died and `tracehook_report_clone` took no action to prevent it from self-reaping.

Called with no locks held.

tracehook_prepare_release_task

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_prepare_release_task` — task is being reaped, clean up tracing

Synopsis

```
void tracehook_prepare_release_task (struct task_struct *
task);
```

Arguments

task

task in `EXIT_DEAD` state

Description

This is called in `release_task` just before `task` gets finally reaped and freed. This would be the ideal place to remove and clean up any tracing-related state for `task`.

Called with no locks held.

tracehook_finish_release_task

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_finish_release_task` — final tracing clean-up

Synopsis

```
void tracehook_finish_release_task (struct task_struct *  
task);
```

Arguments

`task`

task in `EXIT_DEAD` state

Description

This is called in `release_task` when `task` is being in the middle of being reaped. After this, there must be no tracing entanglements.

Called with `write_lock_irq(tasklist_lock)` held.

tracehook_signal_handler

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_signal_handler` — signal handler setup is complete

Synopsis

```
void tracehook_signal_handler (int sig, siginfo_t * info,  
const struct k_sigaction * ka, struct pt_regs * regs, int  
stepping);
```

Arguments

sig

number of signal being delivered

info

siginfo_t of signal being delivered

ka

sigaction setting that chose the handler

regs

user register state

stepping

nonzero if debugger single-step or block-step in use

Description

Called by the arch code after a signal handler has been set up. Register and stack state reflects the user handler about to run. Signal mask changes have already been made.

Called without locks, shortly before returning to user mode (or handling more signals).

tracehook_consider_ignored_signal

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_consider_ignored_signal` — suppress short-circuit of ignored signal

Synopsis

```
int tracehook_consider_ignored_signal (struct task_struct *  
task, int sig, void __user * handler);
```

Arguments

task

task receiving the signal

sig

signal number being sent

handler

SIG_IGN or SIG_DFL

Description

Return zero iff tracing doesn't care to examine this ignored signal, so it can short-circuit normal delivery and never even get queued. Either *handler* is SIG_DFL and *sig*'s default is ignore, or it's SIG_IGN.

Called with *task->sigband->siglock* held.

tracehook_consider_fatal_signal

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_consider_fatal_signal` — suppress special handling of fatal signal

Synopsis

```
int tracehook_consider_fatal_signal (struct task_struct *
task, int sig, void __user * handler);
```

Arguments

task

task receiving the signal

sig

signal number being sent

handler

SIG_DFL or SIG_IGN

Description

Return nonzero to prevent special handling of this termination signal. Normally *handler* is SIG_DFL. It can be SIG_IGN if *sig* is ignored, in which case *force_sig* is about to reset it to SIG_DFL. When this returns zero, this signal might cause a quick termination that does not give the debugger a chance to intercept the signal.

Called with or without *task->sigand->siglock* held.

tracehook_force_sigpending

LINUX

Kernel Hackers Manual February 2009

Name

tracehook_force_sigpending — let tracing force signal_pending(current) on

Synopsis

```
int tracehook_force_sigpending ( void );
```

Arguments

void

no arguments

Description

Called when recomputing our `signal_pending` flag. Return nonzero to force the `signal_pending` flag on, so that `tracehook_get_signal` will be called before the next return to user mode.

Called with `current->sighand->siglock` held.

tracehook_get_signal

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_get_signal` — deliver synthetic signal to traced task

Synopsis

```
int tracehook_get_signal (struct task_struct * task, struct
pt_regs * regs, siginfo_t * info, struct k_sigaction *
return_ka);
```

Arguments

task

current

regs

`task_pt_regs(current)`

info

details of synthetic signal

return_ka

sigaction for synthetic signal

Description

Return zero to check for a real pending signal normally. Return -1 after releasing the siglock to repeat the check. Return a signal number to induce an artificial signal delivery, setting **info* and **return_ka* to specify its details and behavior.

The *return_ka->sa_handler* value controls the disposition of the signal, no matter the signal number. For `SIG_DFL`, the return value is a representative signal to indicate the behavior (e.g. `SIGTERM` for death, `SIGQUIT` for core dump, `SIGSTOP` for job control stop, `SIGTSTP` for stop unless in an orphaned pgrp), but the signal number reported will be *info->si_signo* instead.

Called with *task->sighand->siglock* held, before dequeuing pending signals.

tracehook_notify_jctl

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_notify_jctl` — report about job control stop/continue

Synopsis

```
int tracehook_notify_jctl (int notify, int why);
```

Arguments

notify

nonzero if this is the last thread in the group to stop

why

CLD_STOPPED or CLD_CONTINUED

Description

This is called when we might call `do_notify_parent_cldstop`. It's called when about to stop for job control; we are already in `TASK_STOPPED` state, about to call `schedule`. It's also called when a delayed `CLD_STOPPED` or `CLD_CONTINUED` report is ready to be made.

Return nonzero to generate a `SIGCHLD` with *why*, which is normal if *notify* is nonzero.

Called with no locks held.

tracehook_notify_death

LINUX

Kernel Hackers Manual February 2009

Name

`tracehook_notify_death` — task is dead, ready to notify parent

Synopsis

```
int tracehook_notify_death (struct task_struct * task, void **  
death_cookie, int group_dead);
```

Arguments

task

current task now exiting

death_cookie

value to pass to `tracehook_report_death`

group_dead

nonzero if this was the last thread in the group to die

Description

A return value ≥ 0 means call `do_notify_parent` with that signal number.

Negative return value can be `DEATH_REAP` to self-reap right now, or

`DEATH_DELAYED_GROUP_LEADER` to a zombie without notifying our parent. Note that a return value of 0 means a `do_notify_parent` call that sends no signal, but still wakes up a parent blocked in `wait*`).

Called with `write_lock_irq(tasklist_lock)` held.

tracehook_report_death

LINUX

Name

`tracehook_report_death` — task is dead and ready to be reaped

Synopsis

```
void tracehook_report_death (struct task_struct * task, int
signal, void * death_cookie, int group_dead);
```

Arguments

task

current task now exiting

signal

return value from `tracehook_notify_death`

death_cookie

value passed back from `tracehook_notify_death`

group_dead

nonzero if this was the last thread in the group to die

Description

Thread has just become a zombie or is about to self-reap. If positive, *signal* is the signal number just sent to the parent (usually SIGCHLD). If *signal* is

DEATH_REAP, this thread will self-reap. If *signal* is

DEATH_DELAYED_GROUP_LEADER, this is a delayed_group_leader zombie.

The *death_cookie* was passed back by `tracehook_notify_death`.

If normal reaping is not inhibited, *task->exit_state* might be changing in parallel.

Called without locks.

set_notify_resume

LINUX

Kernel Hackers Manual February 2009

Name

`set_notify_resume` — cause `tracehook_notify_resume` to be called

Synopsis

```
void set_notify_resume (struct task_struct * task);
```

Arguments

task

task that will call `tracehook_notify_resume`

Description

Calling this arranges that *task* will call `tracehook_notify_resume` before returning to user mode. If it's already running in user mode, it will enter the kernel and call `tracehook_notify_resume` soon. If it's blocked, it will not be woken.

tracehook_notify_resume

LINUX

Name

`tracehook_notify_resume` — report when about to return to user mode

Synopsis

```
void tracehook_notify_resume (struct pt_regs * regs);
```

Arguments

regs

user-mode registers of *current* task

Description

This is called when `TIF_NOTIFY_RESUME` has been set. Now we are about to return to user mode, and the user state in *regs* can be inspected or adjusted. The caller in arch code has cleared `TIF_NOTIFY_RESUME` before the call. If the flag gets set again asynchronously, this will be called again before we return to user mode.

Called without locks. However, on some machines this may be called with interrupts disabled.

4.2. Architecture Calls Out

An arch that has done all these things sets `CONFIG_HAVE_ARCH_TRACEHOOK`. This is required to enable the utrace code.

4.2.1. `<asm/ptrace.h>`

An arch defines these in `<asm/ptrace.h>` if it supports hardware single-step or block-step features.

`arch_has_single_step`

LINUX

Kernel Hackers Manual February 2009

Name

`arch_has_single_step` — does this CPU support user-mode single-step?

Synopsis

```
arch_has_single_step (void);
```

Arguments

None

Description

If this is defined, then there must be function declarations or inlines for `user_enable_single_step` and `user_disable_single_step`. `arch_has_single_step` should evaluate to nonzero iff the machine supports instruction single-step for user mode. It can be a constant or it can test a CPU feature bit.

arch_has_block_step

LINUX

Kernel Hackers Manual February 2009

Name

`arch_has_block_step` — does this CPU support user-mode block-step?

Synopsis

```
arch_has_block_step (void);
```

Arguments

None

Description

If this is defined, then there must be a function declaration or inline for `user_enable_block_step`, and `arch_has_single_step` must be defined too. `arch_has_block_step` should evaluate to nonzero iff the machine supports step-until-branch for user mode. It can be a constant or it can test a CPU feature bit.

user_enable_single_step

LINUX

Name

`user_enable_single_step` — single-step in user-mode task

Synopsis

```
void user_enable_single_step (struct task_struct * task);
```

Arguments

task

either current or a task stopped in `TASK_TRACED`

Description

This can only be called when `arch_has_single_step` has returned nonzero. Set *task* so that when it returns to user mode, it will trap after the next single instruction executes. If `arch_has_block_step` is defined, this must clear the effects of `user_enable_block_step` too.

user_enable_block_step

LINUX

Name

`user_enable_block_step` — step until branch in user-mode task

Synopsis

```
void user_enable_block_step (struct task_struct * task);
```

Arguments

task

either current or a task stopped in TASK_TRACED

Description

This can only be called when `arch_has_block_step` has returned nonzero, and will never be called when single-instruction stepping is being used. Set *task* so that when it returns to user mode, it will trap after the next branch or trap taken.

user_disable_single_step

LINUX

Kernel Hackers Manual February 2009

Name

`user_disable_single_step` — cancel user-mode single-step

Synopsis

```
void user_disable_single_step (struct task_struct * task);
```

Arguments

task

either current or a task stopped in `TASK_TRACED`

Description

Clear *task* of the effects of `user_enable_single_step` and `user_enable_block_step`. This can be called whether or not either of those was ever called on *task*, and even if `arch_has_single_step` returned zero.

4.2.2. `<asm/syscall.h>`

An arch provides `<asm/syscall.h>` that defines these as inlines, or declares them as exported functions. These interfaces are described in Section 3.3.

4.2.3. `<linux/tracehook.h>`

An arch must define `TIF_NOTIFY_RESUME` and `TIF_SYSCALL_TRACE` in its `<asm/thread_info.h>`. The arch code must call the following functions, all declared in `<linux/tracehook.h>` and described in Section 4.1:

- `tracehook_notify_resume`
- `tracehook_report_syscall_entry`
- `tracehook_report_syscall_exit`
- `tracehook_signal_handler`