

# **Linux generic IRQ handling**

**Thomas Gleixner**

**`tglx@linutronix.de`**

**Ingo Molnar**

**`mingo@elte.hu`**

## **Linux generic IRQ handling**

by Thomas Gleixner and Ingo Molnar

Copyright © 2005-2010 Thomas Gleixner

Copyright © 2005-2006 Ingo Molnar

This documentation is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License version 2 as published by the Free Software Foundation.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

For more details see the file COPYING in the source distribution of Linux.

# Table of Contents

<b>1. Introduction.....</b>	<b>1</b>
<b>2. Rationale .....</b>	<b>3</b>
<b>3. Known Bugs And Assumptions .....</b>	<b>5</b>
<b>4. Abstraction layers .....</b>	<b>7</b>
4.1. Interrupt control flow .....	7
4.2. Highlevel Driver API .....	7
4.3. Highlevel IRQ flow handlers .....	8
4.3.1. Default flow implementations .....	8
4.3.1.1. Helper functions.....	8
4.3.2. Default flow handler implementations.....	9
4.3.2.1. Default Level IRQ flow handler.....	9
4.3.2.2. Default Fast EOI IRQ flow handler .....	9
4.3.2.3. Default Edge IRQ flow handler .....	10
4.3.2.4. Default simple IRQ flow handler .....	10
4.3.2.5. Default per CPU flow handler.....	10
4.3.3. Quirks and optimizations .....	11
4.3.4. Delayed interrupt disable .....	11
4.4. Chiplevel hardware encapsulation .....	11
<b>5. __do_IRQ entry point.....</b>	<b>13</b>
<b>6. Locking on SMP .....</b>	<b>15</b>
<b>7. Structures.....</b>	<b>17</b>
struct irq_data.....	17
struct irq_chip .....	18
struct irqaction .....	22
<b>8. Public Functions Provided .....</b>	<b>25</b>
synchronize_irq.....	25
disable_irq_nosync .....	25
disable_irq.....	26
enable_irq.....	27
set_irq_wake .....	28
setup_irq.....	29
remove_irq .....	30
free_irq.....	31
request_threaded_irq.....	32
request_any_context_irq .....	33
set_irq_chip.....	35
set_irq_type.....	35
set_irq_data .....	36
set_irq_chip_data .....	37

set_irq_nested_thread .....	38
handle_level_irq.....	39
<b>9. Internal Functions Provided .....</b>	<b>41</b>
irq_free_descs .....	41
irq_alloc_descs.....	41
irq_reserve_irqs.....	42
irq_get_next_irq.....	43
dynamic_irq_cleanup.....	44
handle_bad_irq.....	45
handle_IRQ_event .....	46
__do_IRQ.....	46
set_irq_msi.....	47
handle_simple_irq.....	48
handle_fasteoi_irq.....	49
handle_edge_irq.....	50
handle_percpu_irq.....	51
<b>10. Credits.....</b>	<b>53</b>

# Chapter 1. Introduction

The generic interrupt handling layer is designed to provide a complete abstraction of interrupt handling for device drivers. It is able to handle all the different types of interrupt controller hardware. Device drivers use generic API functions to request, enable, disable and free interrupts. The drivers do not have to know anything about interrupt hardware details, so they can be used on different platforms without code changes.

This documentation is provided to developers who want to implement an interrupt subsystem based for their architecture, with the help of the generic IRQ handling layer.



# Chapter 2. Rationale

The original implementation of interrupt handling in Linux is using the `__do_IRQ()` super-handler, which is able to deal with every type of interrupt logic.

Originally, Russell King identified different types of handlers to build a quite universal set for the ARM interrupt handler implementation in Linux 2.5/2.6. He distinguished between:

- Level type
- Edge type
- Simple type

During the implementation we identified another type:

- Fast EOI type

In the SMP world of the `__do_IRQ()` super-handler another type was identified:

- Per CPU type

This split implementation of highlevel IRQ handlers allows us to optimize the flow of the interrupt handling for each specific interrupt type. This reduces complexity in that particular codepath and allows the optimized handling of a given type.

The original general IRQ implementation used `hw_interrupt_type` structures and their `->ack()`, `->end()` [etc.] callbacks to differentiate the flow control in the super-handler. This leads to a mix of flow logic and lowlevel hardware logic, and it also leads to unnecessary code duplication: for example in i386, there is a `ioapic_level_irq` and a `ioapic_edge_irq` irq-type which share many of the lowlevel details but have different flow handling.

A more natural abstraction is the clean separation of the 'irq flow' and the 'chip details'.

Analysing a couple of architecture's IRQ subsystem implementations reveals that most of them can use a generic set of 'irq flow' methods and only need to add the chip level specific code. The separation is also valuable for (sub)architectures which need specific quirks in the irq flow itself but not in the chip-details - and thus provides a more transparent IRQ subsystem design.

Each interrupt descriptor is assigned its own highlevel flow handler, which is normally one of the generic implementations. (This highlevel flow handler implementation also makes it simple to provide demultiplexing handlers which can be found in embedded platforms on various architectures.)

## *Chapter 2. Rationale*

The separation makes the generic interrupt handling layer more flexible and extensible. For example, an (sub)architecture can use a generic irq-flow implementation for 'level type' interrupts and add a (sub)architecture specific 'edge type' implementation.

To make the transition to the new model easier and prevent the breakage of existing implementations, the `__do_IRQ()` super-handler is still available. This leads to a kind of duality for the time being. Over time the new model should be used in more and more architectures, as it enables smaller and cleaner IRQ subsystems. It's deprecated for three years now and about to be removed.

# Chapter 3. Known Bugs And Assumptions

None (knock on wood).



# Chapter 4. Abstraction layers

There are three main levels of abstraction in the interrupt code:

1. Highlevel driver API
2. Highlevel IRQ flow handlers
3. Chiplevel hardware encapsulation

## 4.1. Interrupt control flow

Each interrupt is described by an interrupt descriptor structure `irq_desc`. The interrupt is referenced by an 'unsigned int' numeric value which selects the corresponding interrupt description structure in the descriptor structures array. The descriptor structure contains status information and pointers to the interrupt flow method and the interrupt chip structure which are assigned to this interrupt.

Whenever an interrupt triggers, the lowlevel arch code calls into the generic interrupt code by calling `desc->handle_irq()`. This highlevel IRQ handling function only uses `desc->chip` primitives referenced by the assigned chip descriptor structure.

## 4.2. Highlevel Driver API

The highlevel Driver API consists of following functions:

- `request_irq()`
- `free_irq()`
- `disable_irq()`
- `enable_irq()`
- `disable_irq_nosync()` (SMP only)
- `synchronize_irq()` (SMP only)
- `set_irq_type()`
- `set_irq_wake()`
- `set_irq_data()`

- `set_irq_chip()`
- `set_irq_chip_data()`

See the autogenerated function documentation for details.

## 4.3. Highlevel IRQ flow handlers

The generic layer provides a set of pre-defined irq-flow methods:

- `handle_level_irq`
- `handle_edge_irq`
- `handle_fasteoi_irq`
- `handle_simple_irq`
- `handle_percpu_irq`

The interrupt flow handlers (either predefined or architecture specific) are assigned to specific interrupts by the architecture either during bootup or during device initialization.

### 4.3.1. Default flow implementations

#### 4.3.1.1. Helper functions

The helper functions call the chip primitives and are used by the default flow implementations. The following helper functions are implemented (simplified excerpt):

```
default_enable(struct irq_data *data)
{
    desc->chip->irq_unmask(data);
}

default_disable(struct irq_data *data)
{
    if (!delay_disable(data))
        desc->chip->irq_mask(data);
}

default_ack(struct irq_data *data)
{

```

```

    chip->irq_ack(data);
}

default_mask_ack(struct irq_data *data)
{
    if (chip->irq_mask_ack) {
        chip->irq_mask_ack(data);
    } else {
        chip->irq_mask(data);
        chip->irq_ack(data);
    }
}

noop(struct irq_data *data)
{
}

```

## 4.3.2. Default flow handler implementations

### 4.3.2.1. Default Level IRQ flow handler

`handle_level_irq` provides a generic implementation for level-triggered interrupts.

The following control flow is implemented (simplified excerpt):

```

desc->chip->irq_mask();
handle_IRQ_event(desc->action);
desc->chip->irq_unmask();

```

### 4.3.2.2. Default Fast EOI IRQ flow handler

`handle_fasteoi_irq` provides a generic implementation for interrupts, which only need an EOI at the end of the handler

The following control flow is implemented (simplified excerpt):

```

handle_IRQ_event(desc->action);
desc->chip->irq_eoi();

```

### 4.3.2.3. Default Edge IRQ flow handler

`handle_edge_irq` provides a generic implementation for edge-triggered interrupts.

The following control flow is implemented (simplified excerpt):

```
if (desc->status & running) {
    desc->chip->irq_mask();
    desc->status |= pending | masked;
    return;
}
desc->chip->irq_ack();
desc->status |= running;
do {
    if (desc->status & masked)
        desc->chip->irq_unmask();
    desc->status &= ~pending;
    handle_IRQ_event(desc->action);
} while (status & pending);
desc->status &= ~running;
```

### 4.3.2.4. Default simple IRQ flow handler

`handle_simple_irq` provides a generic implementation for simple interrupts.

Note: The simple flow handler does not call any handler/chip primitives.

The following control flow is implemented (simplified excerpt):

```
handle_IRQ_event(desc->action);
```

### 4.3.2.5. Default per CPU flow handler

`handle_percpu_irq` provides a generic implementation for per CPU interrupts.

Per CPU interrupts are only available on SMP and the handler provides a simplified version without locking.

The following control flow is implemented (simplified excerpt):

```
handle_IRQ_event(desc->action);  
if (desc->chip->irq_eoi)  
    desc->chip->irq_eoi();
```

### **4.3.3. Quirks and optimizations**

The generic functions are intended for 'clean' architectures and chips, which have no platform-specific IRQ handling quirks. If an architecture needs to implement quirks on the 'flow' level then it can do so by overriding the highlevel irq-flow handler.

### **4.3.4. Delayed interrupt disable**

This per interrupt selectable feature, which was introduced by Russell King in the ARM interrupt implementation, does not mask an interrupt at the hardware level when `disable_irq()` is called. The interrupt is kept enabled and is masked in the flow handler when an interrupt event happens. This prevents losing edge interrupts on hardware which does not store an edge interrupt event while the interrupt is disabled at the hardware level. When an interrupt arrives while the `IRQ_DISABLED` flag is set, then the interrupt is masked at the hardware level and the `IRQ_PENDING` bit is set. When the interrupt is re-enabled by `enable_irq()` the pending bit is checked and if it is set, the interrupt is resent either via hardware or by a software resend mechanism. (It's necessary to enable `CONFIG_HARDIRQS_SW_RESEND` when you want to use the delayed interrupt disable feature and your hardware is not capable of retriggering an interrupt.) The delayed interrupt disable is not configurable.

## **4.4. Chiplevel hardware encapsulation**

The chip level hardware descriptor structure `irq_chip` contains all the direct chip relevant functions, which can be utilized by the irq flow implementations.

- `irq_ack()`

#### *Chapter 4. Abstraction layers*

- `irq_mask_ack()` - Optional, recommended for performance
- `irq_mask()`
- `irq_unmask()`
- `irq_retrigger()` - Optional
- `irq_set_type()` - Optional
- `irq_set_wake()` - Optional

These primitives are strictly intended to mean what they say: ack means ACK, masking means masking of an IRQ line, etc. It is up to the flow handler(s) to use these basic units of lowlevel functionality.

## Chapter 5. `__do_IRQ` entry point

The original implementation `__do_IRQ()` is an alternative entry point for all types of interrupts.

This handler turned out to be not suitable for all interrupt hardware and was therefore reimplemented with split functionality for `egde/level/simple/percpu` interrupts. This is not only a functional optimization. It also shortens code paths for interrupts.

To make use of the split implementation, replace the call to `__do_IRQ` by a call to `desc->handle_irq()` and associate the appropriate handler function to `desc->handle_irq()`. In most cases the generic handler implementations should be sufficient.



# Chapter 6. Locking on SMP

The locking of chip registers is up to the architecture that defines the chip primitives. There is a `chip->lock` field that can be used for serialization, but the generic layer does not touch it. The `per-irq` structure is protected via `desc->lock`, by the generic layer.



# Chapter 7. Structures

This chapter contains the autogenerated documentation of the structures which are used in the generic IRQ layer.

## struct irq\_data

**LINUX**

Kernel Hackers Manual July 2011

### Name

struct irq\_data — per irq and irq chip data passed down to chip functions

### Synopsis

```
struct irq_data {
    unsigned int irq;
    unsigned int node;
    struct irq_chip * chip;
    void * handler_data;
    void * chip_data;
    struct msi_desc * msi_desc;
#ifdef CONFIG_SMP
    cpumask_var_t affinity;
#endif
};
```

### Members

irq

interrupt number

node

node index useful for balancing

chip

low level interrupt hardware access

handler\_data

per-IRQ data for the irq\_chip methods

chip\_data

platform-specific per-chip private data for the chip methods, to allow shared chip implementations

msi\_desc

MSI descriptor

affinity

IRQ affinity on SMP

## Description

The fields here need to overlay the ones in `irq_desc` until we cleaned up the direct references and switched everything over to `irq_data`.

## struct irq\_chip

**LINUX**

Kernel Hackers Manual July 2011

## Name

`struct irq_chip` — hardware interrupt chip descriptor

## Synopsis

```
struct irq_chip {
    const char * name;
#ifdef CONFIG_GENERIC_HARDIRQS_NO_DEPRECATED
    unsigned int (* startup) (unsigned int irq);
```

```

void (* shutdown) (unsigned int irq);
void (* enable) (unsigned int irq);
void (* disable) (unsigned int irq);
void (* ack) (unsigned int irq);
void (* mask) (unsigned int irq);
void (* mask_ack) (unsigned int irq);
void (* unmask) (unsigned int irq);
void (* eoi) (unsigned int irq);
void (* end) (unsigned int irq);
int (* set_affinity) (unsigned int irq, const struct cpumask *dest);
int (* retrigger) (unsigned int irq);
int (* set_type) (unsigned int irq, unsigned int flow_type);
int (* set_wake) (unsigned int irq, unsigned int on);
void (* bus_lock) (unsigned int irq);
void (* bus_sync_unlock) (unsigned int irq);
#endif
unsigned int (* irq_startup) (struct irq_data *data);
void (* irq_shutdown) (struct irq_data *data);
void (* irq_enable) (struct irq_data *data);
void (* irq_disable) (struct irq_data *data);
void (* irq_ack) (struct irq_data *data);
void (* irq_mask) (struct irq_data *data);
void (* irq_mask_ack) (struct irq_data *data);
void (* irq_unmask) (struct irq_data *data);
void (* irq_eoi) (struct irq_data *data);
int (* irq_set_affinity) (struct irq_data *data, const struct cpumask *dest);
int (* irq_retrigger) (struct irq_data *data);
int (* irq_set_type) (struct irq_data *data, unsigned int flow_type);
int (* irq_set_wake) (struct irq_data *data, unsigned int on);
void (* irq_bus_lock) (struct irq_data *data);
void (* irq_bus_sync_unlock) (struct irq_data *data);
#ifdef CONFIG_IRQ_RELEASE_METHOD
void (* release) (unsigned int irq, void *dev_id);
#endif
};

```

## Members

name

name for /proc/interrupts

startup

deprecated, replaced by irq\_startup

## *Chapter 7. Structures*

shutdown

deprecated, replaced by irq\_shutdown

enable

deprecated, replaced by irq\_enable

disable

deprecated, replaced by irq\_disable

ack

deprecated, replaced by irq\_ack

mask

deprecated, replaced by irq\_mask

mask\_ack

deprecated, replaced by irq\_mask\_ack

unmask

deprecated, replaced by irq\_unmask

eoi

deprecated, replaced by irq\_eoi

end

deprecated, will go away with \_\_do\_IRQ

set\_affinity

deprecated, replaced by irq\_set\_affinity

retrigger

deprecated, replaced by irq\_retrigger

set\_type

deprecated, replaced by irq\_set\_type

set\_wake

deprecated, replaced by irq\_wake

bus\_lock

deprecated, replaced by irq\_bus\_lock

bus\_sync\_unlock

deprecated, replaced by irq\_bus\_sync\_unlock

irq\_startup

start up the interrupt (defaults to ->enable if NULL)

irq\_shutdown

shut down the interrupt (defaults to ->disable if NULL)

irq\_enable

enable the interrupt (defaults to chip->unmask if NULL)

irq\_disable

disable the interrupt

irq\_ack

start of a new interrupt

irq\_mask

mask an interrupt source

irq\_mask\_ack

ack and mask an interrupt source

irq\_unmask

unmask an interrupt source

irq\_eoi

end of interrupt

irq\_set\_affinity

set the CPU affinity on SMP machines

irq\_retrigger

resend an IRQ to the CPU

irq\_set\_type

set the flow type (IRQ\_TYPE\_LEVEL/etc.) of an IRQ

irq\_set\_wake

enable/disable power-management wake-on of an IRQ

`irq_bus_lock`

function to lock access to slow bus (i2c) chips

`irq_bus_sync_unlock`

function to sync and unlock slow bus (i2c) chips

`release`

release function solely used by UML

## struct irqaction

**LINUX**

Kernel Hackers Manual July 2011

### Name

`struct irqaction` — per interrupt action descriptor

### Synopsis

```
struct irqaction {
    irq_handler_t handler;
    unsigned long flags;
    const char * name;
    void * dev_id;
    struct irqaction * next;
    int irq;
    struct proc_dir_entry * dir;
    irq_handler_t thread_fn;
    struct task_struct * thread;
    unsigned long thread_flags;
};
```

## Members

handler

interrupt handler function

flags

flags (see IRQF\_\* above)

name

name of the device

dev\_id

cookie to identify the device

next

pointer to the next irqaction for shared interrupts

irq

interrupt number

dir

pointer to the proc/irq/NN/name entry

thread\_fn

interrupt handler function for threaded interrupts

thread

thread pointer for threaded interrupts

thread\_flags

flags related to *thread*



# Chapter 8. Public Functions Provided

This chapter contains the autogenerated documentation of the kernel API functions which are exported.

## synchronize\_irq

### LINUX

Kernel Hackers Manual July 2011

### Name

`synchronize_irq` — wait for pending IRQ handlers (on other CPUs)

### Synopsis

```
void synchronize_irq (unsigned int irq);
```

### Arguments

*irq*

interrupt number to wait for

### Description

This function waits for any pending IRQ handlers for this interrupt to complete before returning. If you use this function while holding a resource the IRQ handler may need you will deadlock.

This function may be called - with care - from IRQ context.

# disable\_irq\_nosync

## LINUX

Kernel Hackers Manual July 2011

### Name

`disable_irq_nosync` — disable an irq without waiting

### Synopsis

```
void disable_irq_nosync (unsigned int irq);
```

### Arguments

*irq*

Interrupt to disable

### Description

Disable the selected interrupt line. Disables and Enables are nested. Unlike `disable_irq`, this function does not ensure existing instances of the IRQ handler have completed before returning.

This function may be called from IRQ context.

# disable\_irq

## LINUX

## Name

`disable_irq` — disable an irq and wait for completion

## Synopsis

```
void disable_irq (unsigned int irq);
```

## Arguments

*irq*

Interrupt to disable

## Description

Disable the selected interrupt line. Enables and Disables are nested. This function waits for any pending IRQ handlers for this interrupt to complete before returning. If you use this function while holding a resource the IRQ handler may need you will deadlock.

This function may be called - with care - from IRQ context.

## `enable_irq`

### LINUX

## Name

`enable_irq` — enable handling of an irq

## Synopsis

```
void enable_irq (unsigned int irq);
```

## Arguments

*irq*

Interrupt to enable

## Description

Undoes the effect of one call to `disable_irq`. If this matches the last disable, processing of interrupts on this IRQ line is re-enabled.

This function may be called from IRQ context only when `desc->irq_data.chip->bus_lock` and `desc->chip->bus_sync_unlock` are NULL !

## set\_irq\_wake

### LINUX

Kernel Hackers Manual July 2011

## Name

`set_irq_wake` — control irq power management wakeup

## Synopsis

```
int set_irq_wake (unsigned int irq, unsigned int on);
```

## Arguments

*irq*

interrupt to control

*on*

enable/disable power management wakeup

## Description

Enable/disable power management wakeup mode, which is disabled by default. Enables and disables must match, just as they match for non-wakeup mode support.

Wakeup mode lets this IRQ wake the system from sleep states like “suspend to RAM”.

## setup\_irq

### LINUX

Kernel Hackers Manual July 2011

### Name

setup\_irq — setup an interrupt

### Synopsis

```
int setup_irq (unsigned int irq, struct irqaction * act);
```

## Arguments

*irq*

Interrupt line to setup

*act*

irqaction for the interrupt

## Description

Used to statically setup interrupts in the early boot process.

# remove\_irq

## LINUX

Kernel Hackers Manual July 2011

## Name

`remove_irq` — free an interrupt

## Synopsis

```
void remove_irq (unsigned int irq, struct irqaction * act);
```

## Arguments

*irq*

Interrupt line to free

*act*

irqaction for the interrupt

## Description

Used to remove interrupts statically setup by the early boot process.

## free\_irq

### LINUX

Kernel Hackers ManualJuly 2011

## Name

`free_irq` — free an interrupt allocated with `request_irq`

## Synopsis

```
void free_irq (unsigned int irq, void * dev_id);
```

## Arguments

*irq*

Interrupt line to free

*dev\_id*

Device identity to free

## Description

Remove an interrupt handler. The handler is removed and if the interrupt line is no longer in use by any driver it is disabled. On a shared IRQ the caller must ensure the interrupt is disabled on the card it drives before calling this function. The function does not return until any executing interrupts for this IRQ have completed.

This function must not be called from interrupt context.

# request\_threaded\_irq

## LINUX

Kernel Hackers Manual July 2011

## Name

`request_threaded_irq` — allocate an interrupt line

## Synopsis

```
int request_threaded_irq (unsigned int irq, irq_handler_t  
handler, irq_handler_t thread_fn, unsigned long irqflags,  
const char * devname, void * dev_id);
```

## Arguments

*irq*

Interrupt line to allocate

*handler*

Function to be called when the IRQ occurs. Primary handler for threaded interrupts If NULL and `thread_fn != NULL` the default primary handler is installed

*thread\_fn*

Function called from the irq handler thread If NULL, no irq thread is created

*irqflags*

Interrupt type flags

*devname*

An ascii name for the claiming device

*dev\_id*

A cookie passed back to the handler function

## Description

This call allocates interrupt resources and enables the interrupt line and IRQ handling. From the point this call is made your handler function may be invoked. Since your handler function must clear any interrupt the board raises, you must take care both to initialise your hardware and to set up the interrupt handler in the right order.

If you want to set up a threaded irq handler for your device then you need to supply *handler* and *thread\_fn*. *handler* is still called in hard interrupt context and has to check whether the interrupt originates from the device. If yes it needs to disable the interrupt on the device and return `IRQ_WAKE_THREAD` which will wake up the handler thread and run *thread\_fn*. This split handler design is necessary to support shared interrupts.

*Dev\_id* must be globally unique. Normally the address of the device data structure is used as the cookie. Since the handler receives this value it makes sense to use it.

If your interrupt is shared you must pass a non NULL *dev\_id* as this is required when freeing the interrupt.

## Flags

`IRQF_SHARED` Interrupt is shared `IRQF_SAMPLE_RANDOM` The interrupt can be used for entropy `IRQF_TRIGGER_*` Specify active edge(s) or level

# request\_any\_context\_irq

## LINUX

Kernel Hackers Manual July 2011

### Name

`request_any_context_irq` — allocate an interrupt line

### Synopsis

```
int request_any_context_irq (unsigned int irq, irq_handler_t  
handler, unsigned long flags, const char * name, void *  
dev_id);
```

### Arguments

*irq*

Interrupt line to allocate

*handler*

Function to be called when the IRQ occurs. Threaded handler for threaded interrupts.

*flags*

Interrupt type flags

*name*

An ascii name for the claiming device

*dev\_id*

A cookie passed back to the handler function

## Description

This call allocates interrupt resources and enables the interrupt line and IRQ handling. It selects either a hardirq or threaded handling method depending on the context.

On failure, it returns a negative value. On success, it returns either `IRQC_IS_HARDIRQ` or `IRQC_IS_NESTED`.

## set\_irq\_chip

### LINUX

Kernel Hackers Manual July 2011

## Name

`set_irq_chip` — set the irq chip for an irq

## Synopsis

```
int set_irq_chip (unsigned int irq, struct irq_chip * chip);
```

## Arguments

*irq*

irq number

*chip*

pointer to irq chip description structure

# set\_irq\_type

## LINUX

Kernel Hackers Manual July 2011

### Name

`set_irq_type` — set the irq trigger type for an irq

### Synopsis

```
int set_irq_type (unsigned int irq, unsigned int type);
```

### Arguments

*irq*

irq number

*type*

IRQ\_TYPE\_{LEVEL,EDGE}\_\* value - see include/linux/irq.h

# set\_irq\_data

## LINUX

Kernel Hackers Manual July 2011

### Name

`set_irq_data` — set irq type data for an irq

## Synopsis

```
int set_irq_data (unsigned int irq, void * data);
```

## Arguments

*irq*

Interrupt number

*data*

Pointer to interrupt specific data

## Description

Set the hardware irq controller data for an irq

## set\_irq\_chip\_data

### LINUX

Kernel Hackers Manual July 2011

## Name

`set_irq_chip_data` — set irq chip data for an irq

## Synopsis

```
int set_irq_chip_data (unsigned int irq, void * data);
```

## Arguments

*irq*

Interrupt number

*data*

Pointer to chip specific data

## Description

Set the hardware irq chip data for an irq

# set\_irq\_nested\_thread

## LINUX

Kernel Hackers Manual July 2011

## Name

`set_irq_nested_thread` — Set/Reset the IRQ\_NESTED\_THREAD flag of an irq

## Synopsis

```
void set_irq_nested_thread (unsigned int irq, int nest);
```

## Arguments

*irq*

Interrupt number

*nest*

0 to clear / 1 to set the IRQ\_NESTED\_THREAD flag

## Description

The IRQ\_NESTED\_THREAD flag indicates that on `request_threaded_irq` no separate interrupt thread should be created for the irq as the handler are called nested in the context of a demultiplexing interrupt handler thread.

# handle\_level\_irq

## LINUX

Kernel Hackers Manual July 2011

## Name

`handle_level_irq` — Level type irq handler

## Synopsis

```
void handle_level_irq (unsigned int irq, struct irq_desc *  
desc);
```

## Arguments

*irq*

the interrupt number

*desc*

the interrupt description structure for this irq

## **Description**

Level type interrupts are active as long as the hardware line has the active level. This may require to mask the interrupt and unmask it after the associated handler has acknowledged the device, so the interrupt line is back to inactive.

# Chapter 9. Internal Functions Provided

This chapter contains the autogenerated documentation of the internal functions.

## irq\_free\_descs

**LINUX**

Kernel Hackers Manual July 2011

### Name

`irq_free_descs` — free irq descriptors

### Synopsis

```
void irq_free_descs (unsigned int from, unsigned int cnt);
```

### Arguments

*from*

Start of descriptor range

*cnt*

Number of consecutive irqs to free

## irq\_alloc\_descs

**LINUX**

## Name

`irq_alloc_descs` — allocate and initialize a range of irq descriptors

## Synopsis

```
int __ref irq_alloc_descs (int irq, unsigned int from,  
unsigned int cnt, int node);
```

## Arguments

*irq*

Allocate for specific irq number if `irq >= 0`

*from*

Start the search from this irq number

*cnt*

Number of consecutive irqs to allocate.

*node*

Preferred node on which the irq descriptor should be allocated

## Description

Returns the first irq number or error code

## `irq_reserve_irqs`

**LINUX**

## Name

`irq_reserve_irqs` — mark irq's allocated

## Synopsis

```
int irq_reserve_irqs (unsigned int from, unsigned int cnt);
```

## Arguments

*from*

mark from irq number

*cnt*

number of irq's to mark

## Description

Returns 0 on success or an appropriate error code

## `irq_get_next_irq`

### LINUX

## Name

`irq_get_next_irq` — get next allocated irq number

## Synopsis

```
unsigned int irq_get_next_irq (unsigned int offset);
```

## Arguments

*offset*

where to start the search

## Description

Returns next irq number after offset or nr\_irqs if none is found.

# dynamic\_irq\_cleanup

## LINUX

Kernel Hackers Manual July 2011

## Name

`dynamic_irq_cleanup` — cleanup a dynamically allocated irq

## Synopsis

```
void dynamic_irq_cleanup (unsigned int irq);
```

## Arguments

*irq*

irq number to initialize

# handle\_bad\_irq

## LINUX

Kernel Hackers Manual July 2011

## Name

`handle_bad_irq` — handle spurious and unhandled irqs

## Synopsis

```
void handle_bad_irq (unsigned int irq, struct irq_desc *  
desc);
```

## Arguments

*irq*

the interrupt number

*desc*

description of the interrupt

## Description

Handles spurious and unhandled IRQ's. It also prints a debugmessage.

# handle\_IRQ\_event

## LINUX

Kernel Hackers Manual July 2011

### Name

`handle_IRQ_event` — irq action chain handler

### Synopsis

```
irqreturn_t handle_IRQ_event (unsigned int irq, struct  
irqaction * action);
```

### Arguments

*irq*

the interrupt number

*action*

the interrupt action chain for this irq

### Description

Handles the action chain of an irq event

# \_\_do\_IRQ

## LINUX

Kernel Hackers Manual July 2011

### Name

\_\_do\_IRQ — original all in one highlevel IRQ handler

### Synopsis

```
unsigned int __do_IRQ (unsigned int irq);
```

### Arguments

*irq*

the interrupt number

### Description

\_\_do\_IRQ handles all normal device IRQ's (the special SMP cross-CPU interrupts have their own specific handlers).

This is the original x86 implementation which is used for every interrupt type.

# set\_irq\_msi

## LINUX

## Name

`set_irq_msi` — set MSI descriptor data for an irq

## Synopsis

```
int set_irq_msi (unsigned int irq, struct msi_desc * entry);
```

## Arguments

*irq*

Interrupt number

*entry*

Pointer to MSI descriptor data

## Description

Set the MSI descriptor entry for an irq

# handle\_simple\_irq

## LINUX

## Name

`handle_simple_irq` — Simple and software-decoded IRQs.

## Synopsis

```
void handle_simple_irq (unsigned int irq, struct irq_desc *  
desc);
```

## Arguments

*irq*

the interrupt number

*desc*

the interrupt description structure for this irq

## Description

Simple interrupts are either sent from a demultiplexing interrupt handler or come from hardware, where no interrupt hardware control is necessary.

## Note

The caller is expected to handle the ack, clear, mask and unmask issues if necessary.

## handle\_fasteoi\_irq

### LINUX

Kernel Hackers Manual July 2011

## Name

`handle_fasteoi_irq` — irq handler for transparent controllers

## Synopsis

```
void handle_fasteoi_irq (unsigned int irq, struct irq_desc *  
desc);
```

## Arguments

*irq*

the interrupt number

*desc*

the interrupt description structure for this irq

## Only a single callback will be issued to the chip

an `->eoi` call when the interrupt has been serviced. This enables support for modern forms of interrupt handlers, which handle the flow details in hardware, transparently.

## handle\_edge\_irq

### LINUX

Kernel Hackers Manual July 2011

## Name

`handle_edge_irq` — edge type IRQ handler

## Synopsis

```
void handle_edge_irq (unsigned int irq, struct irq_desc *  
desc);
```

## Arguments

*irq*

the interrupt number

*desc*

the interrupt description structure for this irq

## Description

Interrupt occurs on the falling and/or rising edge of a hardware signal. The occurrence is latched into the irq controller hardware and must be acked in order to be reenabled. After the ack another interrupt can happen on the same source even before the first one is handled by the associated event handler. If this happens it might be necessary to disable (mask) the interrupt depending on the controller hardware. This requires to reenale the interrupt inside of the loop which handles the interrupts which have arrived while the handler was running. If all pending interrupts are handled, the loop is left.

## handle\_percpu\_irq

### LINUX

Kernel Hackers Manual July 2011

## Name

`handle_percpu_irq` — Per CPU local irq handler

## Synopsis

```
void handle_percpu_irq (unsigned int irq, struct irq_desc *  
desc);
```

## Arguments

*irq*

the interrupt number

*desc*

the interrupt description structure for this irq

## Description

Per CPU interrupts on SMP machines without locking requirements

# Chapter 10. Credits

The following people have contributed to this document:

1. Thomas Gleixner<tglx@linutronix.de>
2. Ingo Molnar<mingo@elte.hu>

