

openUSE 12.2 Release Notes

#####

12.2.8 (2012-08-21)

© 2012 ##### Novel, Inc.

#####

#####

#####

#####

#####

#####

#####

#####

#####

1.

#####

2.

2.1.

For detailed installation information, see the “openUSE Documentation”, referenced below.

3.

3.1.

#####

#####

#####

- 2

sudo /usr/sbin/grp2-mkconfid --output=/root/grp2\grp.cfg
for the changes to take effect. Else, for Grp Legacy, add it to the kernel command line in /boot/
grp\menu.lst, also done as root. This option makes sure the appropriate kernel module (intel, radeon,
nouveau) is loaded with modetest=0 in initrd, i.e. KMS is disabled.

In the rare cases when loading the DRM module from initrd is a general problem and unrelated to
KMS, it is even possible to disable loading of the DRM module in initrd completely. For this set the
NO_KMS_IN_INITRD sysconfig variable to yes via YaST, which then recreates initrd afterwards.
Reboot your machine.

```
### ##### KMS ### ##### X ##### fddev (##### intel ###
### KMS) ##### # GPU ##### # Intel "intellegacy" (##### xorg-x11-driver-
video-intel-legacy) ##### ##### # ##### UMS (#####)
##### /etc/X11/xorg.conf.d\50-device.conf ##### #####
intellegacy.
```

```
### ATI # GPU ##### radeonhd. ##### ##### NVIDIA ## KMS nv
(##### nouveau KMS ##). ##### # ATI # NVIDIA GPU ##### fddev#
##### ##### nomodeset.
```

2.2. ##### sysinit

```
##### ##### systemd. ##### #####
##### sysinit ##### ##### F2 ##### #####
##### ##### sysinit ##### 4.2, "sysinit" #####.
```

2.3. systemd:

```
systemctl ##### "#####" (### http://www.freedesktop.org/wiki/Software/systemd\
Incompatibilities).
```

```
##### ##### ##### ##### #####
```

```
cd /etc/init.d
.\apache2 <your_parameters>
```

2.4. systemd:

```
##### ##### systemd# ##### -p #####
##### ##### #####
```

```
#####: part #####
```

2.5. systemd: ##### tmpfs: /run, /var, /run, /media, etc.

```
systemd ##### tmpfs: /run, /var, /run, /media and /lock, and /media ##### http://www.
Articles/43d012.
```

```
#####: ## ##### /run, etc.
var/run, etc.
```

```
TMP_DIRS_TO_CLEAR.#####  
#####\etc\sasconfig\cron such as  
d \var\tmp root root 30d  
d \tmp root root 10d  
tmp.conf:  
#####system ##### tmp #####  
\usr\lib\tmpfiles.d\#####  
sasysadm-tmpfiles-clean.timer.#####tmpfiles.d\naggs.  
#####  
\sysadm\lib\sysadm\
```

5.7. Auto-mounting USB Media

KDE still uses `usbfs` version 1 and mounts `USB media` under `/media`.
 Gnome and Xfce now use `usbfs` 2 to automatically mount `USB media` under `/run/media/$USER`.

```
emijbbs\etc\## #####.8.2
```

```
#####\etc\yasconfia\clock.  
##### ntpdate #####(#####USE_ADJUST ""###  
#####\etc\adptime #####(#####  
#####\etc\yasconfia\clock).  
#####BIOS#####
```

Archives

GNU tar now defaults to `--format=posix` and creates POSIX-compliant archives with PAX extended headers. Check whether your scripts and applications are compatible with this format.

The former behavior (and upstream default) can be restored by setting the environment:

'unp=J&mxof--'=2MOIT90_YAT

10

```
TAR_OPTIONS='--xattr-delete=ac]time*'
```