

---

# openSUSE 12.3 Release Notes

Version: 12.3.11 (2013-08-22)

Copyright © 2013 Novell, Inc.

Ave#i permisiunea de a copia, distribui #i/sau modifica acest document în condi#iile GNU Free Documentation License, versiunea 1.2 sau orice versiune ulterioar# publicat# de Free Software Foundation; f#r# Sec#iuni Invariante, f#r# Texte pentru Coperta I (Front-Cover) #i f#r# Texte pentru Coperta II (Back-Cover). O copie a acestei licen#e este inclus# în fi#ierul `fdl.txt`.

1. Diverse .....	2
2. Instalare .....	2
2.1. For Detailed Installation Information .....	2
2.2. No Network after Installation .....	2
2.3. The Proprietary NVIDIA Driver Requires Users to Have Access to <code>/dev/nvidia*</code> Devi- ces .....	2
2.4. Non-existent Floppy Drive Enabled in BIOS Causes Hang .....	2
3. General .....	2
3.1. Documenta#ia openSUSE .....	2
3.2. UEFI—Unified Extensible Firmware Interface .....	3
3.3. Enable Secure Boot in YaST Not Enabled by Default When in Secure Boot Mode .....	3
3.4. Wrong Bootloader When Installing from a Live Medium in a UEFI Environment .....	3
3.5. openSUSE 12.3 Medium May Not Boot on Future Secure Boot Enabled Hardware .....	3
3.6. Crypted LVM in UEFI Mode Needs <code>/boot</code> Partition .....	4
4. Actualizare sistem .....	4
4.1. Sysvinit Support No Longer Available .....	4
4.2. systemd: Activating NetworkManager with a <code>network.service</code> Alias Link .....	4
4.3. <code>SYSLOG_DAEMON</code> Variable Removed .....	5
5. Detalii tehnice .....	5
5.1. Ini#ializarea graficii cu KMS (Kernel Mode Setting) .....	5
5.2. systemd: Se cur### directoarele ( <code>/tmp</code> #i <code>/var/tmp</code> ) .....	6
5.3. systemd: Persistent Journal across Reboots .....	6
5.4. <code>pwdutils</code> Replaced by <code>shadow</code> .....	6
5.5. Configuring Postfix .....	6
5.6. GTK+ Applications Output a <code>Fontconfig</code> Warning .....	6
5.7. GNOME: Workaround to Set Shift or Ctrl+Shift as Shortcut Keys for Input Source Se- lection .....	6
5.8. SSH Installation Blocked by <code>SuSEFirewall</code> Service .....	7

Dac# actualiza#i o versiune mai veche la aceast# versiune openSUSE, consulta#i aici notele de lansare anterioare: [http://en.opensuse.org/openSUSE:Release\\_Notes](http://en.opensuse.org/openSUSE:Release_Notes)

Aceste informa#ii despre produs acoper# urm#toarele aspecte:

- Sec#iune 1, „Diverse”: These entries are automatically included from openFATE, the Feature- and Requirements Management System (<http://features.opensuse.org>).

Indisponibil

- Sec#iune 2, „Instalare”: Citi#i acestea dac# dori#i s# instala#i sistemul din buc##i.
- Sec#iune 3, „General”: Informa#ie pe care fiecare ar trebui s# o citeasc#.
- Sec#iune 4, „Actualizare sistem”: Issues related to the process if you run a system upgrade from the previous release to this openSUSE version.

- Secțiune 5, „Detalii tehnice”: Această secțiune conține un număr de schimbări tehnice și îmbunătățiri pentru utilizatorul experimentat.

## 1. Diverse

Indisponibil

## 2. Instalare

### 2.1. For Detailed Installation Information

For detailed installation information, see Secțiune 3.1, „Documentația openSUSE”.

### 2.2. No Network after Installation

Directly after installation, NetworkManager is not started automatically and thus WiFi cannot be configured. To enable networking (WiFi), reboot the machine once manually.

### 2.3. The Proprietary NVIDIA Driver Requires Users to Have Access to /dev/nvidia\* Devices

Default and new users are no longer added to the `video` group automatically. But the proprietary NVIDIA driver requires users to have access to `/dev/nvidia*` devices.

Symptoms: OpenGL applications report that they cannot operate on `/dev/nvidiactl`. Or GNOME only showing a blank screen with a mouse pointer.

Because the NVIDIA driver does not use the usual kernel methods that allow to install ACLs on the device nodes, users have to be added manually to the `video` group; as `root` call (replace `$USER` with the actual username):

```
usermod -a -G video $USER
```

### 2.4. Non-existent Floppy Drive Enabled in BIOS Causes Hang

If a floppy drive support is enabled in the BIOS, but does not actually exist in the machine, it can cause hangs during the installation while YaST is searching for partitions.

To avoid this issue, disable floppy drive support in the BIOS.

## 3. General

### 3.1. Documentația openSUSE

- In *Start-Up*, find step-by-step installation instructions, as well as introductions to the KDE and Gnome desktops and to the LibreOffice suite. Also covered are basic administration topics such as deployment and software management and an introduction to the bash shell.

- *Reference* covers administration, and system configuration in detail and explains how to set up various network services.
- The *Security Guide* introduces basic concepts of system security, covering both local and network security aspects.
- The *System Analysis and Tuning Guide* helps with problem detection, resolution and optimization.
- *Virtualization with KVM* offers an introduction to setting up and managing virtualization with KVM, libvirt and QEMU tools.

Find the documentation in `/usr/share/doc/manual/opensuse-manuals_${LANG}` after installing the package `opensuse-manuals_${LANG}`, or online on <http://doc.opensuse.org>.

## 3.2. UEFI—Unified Extensible Firmware Interface

Prior to installing openSUSE on a system that boots using UEFI (Unified Extensible Firmware Interface) you are urgently advised to check for any firmware updates the hardware vendor recommends and, if available, to install such an update. A pre-installed Windows 8 is a strong indication that your system boots using UEFI.

*Background:* Some UEFI firmware has bugs that cause it to break if too much data gets written to the UEFI storage area. Nobody really knows how much "too much" is, though. openSUSE minimizes the risk by not writing more than the bare minimum required to boot the OS. The minimum means telling the UEFI firmware about the location of the openSUSE boot loader. Upstream Linux Kernel features that use the UEFI storage area for storing boot and crash information (`pstore`) have been disabled by default. Nevertheless it is recommended to install any firmware updates the hardware vendor recommends.

## 3.3. Enable Secure Boot in YaST Not Enabled by Default When in Secure Boot Mode

This only affects machines in UEFI mode with secure boot enabled.

YaST does not automatically detect if the machine has secure boot enabled and will therefore install an unsigned bootloader by default. But the unsigned bootloader will not be accepted by the firmware. To have a signed bootloader installed the option "Enable Secure Boot" has to be manually enabled.

## 3.4. Wrong Bootloader When Installing from a Live Medium in a UEFI Environment

This only affects machines in UEFI mode.

When using the installer on the live medium, YaST does not detect UEFI mode and therefore installs the legacy bootloader. This results in a not bootable system. The bootloader has to be switched from `grub2` to `grub2-efi` manually.

## 3.5. openSUSE 12.3 Medium May Not Boot on Future Secure Boot Enabled Hardware

This only affects machines in UEFI mode.

Our double signed shim on openSUSE 12.3 medium may be rejected by future firmwares.

If the openSUSE 12.3 medium does not boot on future secure boot enabled hardware, temporarily disable secure boot, install openSUSE and apply all online updates to get an updated shim.

After installing all updates secure boot can be turned on again.

## 3.6. Crypted LVM in UEFI Mode Needs /boot Partition

This only affects installations in UEFI mode.

In the partitioning proposal when checking the option to use LVM (which is required for full disk encryption) YaST does not create a separate `/boot` partition. That means kernel and `initrd` end up in the (potentially encrypted) LVM container, inaccessible to the boot loader. To get full disk encryption when using UEFI, partitioning has to be done manually.

# 4. Actualizare sistem

## 4.1. Sysvinit Support No Longer Available

`sysvinit` is no longer supported in this release. It has been deprecated since the last two releases.

## 4.2. systemd: Activating NetworkManager with a network.service Alias Link

By default, you use the YaST Network Settings dialog (**yast2 network**) to activate NetworkManager. If you want to activate NetworkManager, proceed as follows.

The `NETWORKMANAGER` sysconfig variable in `/etc/sysconfig/network/config` to activate NetworkManager has been replaced with a `systemd network.service` alias link, which will be created with the

```
systemctl enable NetworkManager.service
```

command. It causes the creation of a `network.service` alias link pointing to the `NetworkManager.service`, and thus deactivates the `/etc/init.d/network` script. The command

```
systemctl -p Id show network.service
```

allows to query the currently selected network service.

To enable NetworkManager, use:

- First, stop the running service:

```
systemctl is-active network.service && \
systemctl stop network.service
```

- Enable the NetworkManager service:

```
systemctl --force enable NetworkManager.service
```

- Start the NetworkManager service (via alias link):

```
systemctl start network.service
```

To disable NetworkManager, use:

- Stop the running service:

```
systemctl is-active network.service && \  
systemctl stop network.service
```

- Disable the NetworkManager service:

```
systemctl disable NetworkManager.service
```

- Start the **/etc/init.d/network** service:

```
systemctl start network.service
```

To query the currently selected service, use:

```
systemctl -p Id show network.service
```

It returns "Id=NetworkManager.service" if the NetworkManager service is enabled, otherwise "Id=network.service" and **/etc/init.d/network** is acting as the network service.

## 4.3. SYSLOG\_DAEMON Variable Removed

The SYSLOG\_DAEMON variable has been removed. Previously, it was used to select the syslog daemon. Starting with openSUSE 12.3, only one syslog implementation can be installed at a time on a system and will be selected automatically for usage.

For details, see the `syslog(8)` manpage.

# 5. Detalii tehnice

## 5.1. Inițializarea graficii cu KMS (Kernel Mode Setting)

With openSUSE 11.3 we switched to KMS (Kernel Mode Setting) for Intel, ATI and NVIDIA graphics, which now is our default. If you encounter problems with the KMS driver support (intel, radeon, nouveau), disable KMS by adding `nomodeset` to the kernel boot command line. To set this permanently using Grub 2, the default boot loader, add it to the `GRUB_CMDLINE_LINUX_DEFAULT` kernel default load options line in your `/etc/default/grub` text file as root and running the terminal command

```
sudo /usr/sbin/grub2-mkconfig --output=/boot/grub2/grub.cfg
```

for the changes to take effect. Else, for Grub Legacy, add it to the kernel command line in `/boot/grub/menu.lst`, also done as root. This option makes sure the appropriate kernel module (intel, radeon, nouveau) is loaded with `modeset=0` in `initrd`, i.e. KMS is disabled.

In the rare cases when loading the DRM module from `initrd` is a general problem and unrelated to KMS, it is even possible to disable loading of the DRM module in `initrd` completely. For this set the `NO_KMS_IN_INITRD` sysconfig variable to `yes` via YaST, which then recreates `initrd` afterwards. Reboot your machine.

On Intel without KMS the Xserver falls back to the `fbdev` driver (the `intel` driver only supports KMS); alternatively, for legacy GPUs from Intel the "intellegacy" driver (`xorg-x11-driver-video-intel-legacy` package) is available, which still supports UMS (User Mode Setting). To use it, edit `/etc/X11/xorg.conf.d/50-device.conf` and change the driver entry to `intellegacy`.

On ATI for current GPUs it falls back to `radeonhd`. On NVIDIA without KMS the `nv` driver is used (the nouveau driver supports only KMS). Note, newer ATI and NVIDIA GPUs are falling back to `fbdev`, if you specify the `nomodeset` kernel boot parameter.

## 5.2. systemd: Se cur### directoarele (/tmp #i /var/tmp)

By default, `systemd` cleans `tmp` directories daily as configured in `/usr/lib/tmpfiles.d/tmp.conf`. Users can change it by copying `/usr/lib/tmpfiles.d/tmp.conf` to `/etc/tmpfiles.d/tmp.conf` and modifying the copied file. It will override `/usr/lib/tmpfiles.d/tmp.conf`.

Note: `systemd` does not honor obsolete `sysconfig` variables in `/etc/sysconfig/cron` such as `TMP_DIRS_TO_CLEAR`.

## 5.3. systemd: Persistent Journal across Reboots

On openSUSE 12.3, the `systemd` journal is not persistent across reboots. If you want to enable journal persistence, either create the `/var/log/journal` directory (as root) or install the `systemd-logger` package. Installing `systemd-logger` package will signal a conflict with other `syslog` implementations, and thus ensuring that the system uses only the `systemd` journal, if installed.

If your system has been upgraded from openSUSE 12.2 (where `/var/log/journal` was created by default) and if you want to disable journal persistence, just remove the `/var/log/journal` directory.

## 5.4. pwutils Replaced by shadow

The `pwutils` package was replaced by the `shadow` package. The `shadow` package is mostly a drop-in replacement, but some commandline options have been removed or changed. See `/usr/share/doc/packages/shadow/README.changes-pwutils` for a list of all the changes.

## 5.5. Configuring Postfix

The `SuSEconfig.postfix` was renamed as `/usr/sbin/config.postfix`. If you set `sysconfig` variables in `/etc/sysconfig/postfix` or `/etc/sysconfig/mail`, you must manually run `/usr/sbin/config.postfix` as root.

## 5.6. GTK+ Applications Output a Fontconfig Warning

Because the location of the `fontconfig` files was changed, Emacs and other applications linked against GTK+ output warning messages when started.

Move the files to the new location:

```
mkdir -p ~/.config/fontconfig
mv ~/.fonts.conf ~/.config/fontconfig/fonts.conf
```

## 5.7. GNOME: Workaround to Set Shift or Ctrl+Shift as Shortcut Keys for Input Source Selection

In Gnome 3.6 use the following workaround to set `Shift` or `Ctrl+Shift` as shortcut keys for input source selection:

1. Install `gnome-tweak-tool`.
2. Start `gnome-tweak-tool` ('Activities'>'advanced settings').
3. Via the left menu, select 'Typing', in the right window, change the settings.

This is also being tracked in the upstream bug report [https://bugzilla.gnome.org/show\\_bug.cgi?id=689839](https://bugzilla.gnome.org/show_bug.cgi?id=689839).

## 5.8. SSH Installation Blocked by SuSEFirewall Service

During the second stage of an SSH installation YaST freezes. It is blocked by the SuSEFirewall service because the `SYSTEMCTL_OPTIONS` environment variable is not set properly.

Workaround: When logged in for the second time to start the second stage of the SSH installation, call **yast.ssh** with the `--ignore-dependencies` as follows:

```
SYSTEMCTL_OPTIONS=--ignore-dependencies yast.ssh
```