



## Release Notes

---

### openSUSE 13.2

openSUSE is a free and Linux-based operating system for your PC, Laptop or Server. You can surf the web, manage your e-mails and photos, do office work, play videos or music and have a lot of fun!

رشن نل ا خيرات: 2017-01-17, : 13.2.20170117

### تايوت حمل ا

- 1 ##### 2
- 2 ### 4
- 3 ##### ##### 5
- 4 ##### 5
- 5 ##### 9
- 6 ##### ## ##### 9

The end of the maintenance period for openSUSE 13.2 is now reached. To keep your systems up to date and secure, migrate to a current openSUSE version.

For more information about upgrading to a current openSUSE version, see <http://en.opensuse.org/SDB:Distribution-Upgrade>. Make sure that all maintenance updates for openSUSE 13.2 are applied before starting the update.

رادصإلا تاظحال م رظنا openSUSE، اذه إلا م يدق رادصإ نم ةيقرتل اب تمق اذا  
ان ه ةجر دمل اق باسل [http://en.opensuse.org/openSUSE:Release\\_Notes](http://en.opensuse.org/openSUSE:Release_Notes)

## 1 تيبتلا

### 1.1 Live CD Installer and Keyboard Settings

The Live CD installer presents a problem related with the keyboard settings. If the user changes from the QWERTY keyboard layout (the default en-US variant), this setting will not be properly applied, and the new system will stay with a QWERTY pre-configuration.

As a workaround, use the **localectl** command-line tool after the installation. For example (to install a German keyboard layout):

```
localectl set-x11-keymap de pc105 nodeadkeys
```

This issue is not present in the DVD Installer.

### 1.2 Network After an Update With YaST

After updating from 13.1 to 13.2 using YaST, there are good chances that the new Wicked network method is running together with the old NetworkManager, if you are using a laptop with a wifi connection.

To solve this, first disable Wicked and enable again NetworkManager:

```
systemctl is-active network.service && systemctl stop network.service  
systemctl is-active wicked.service && systemctl stop wicked.service
```

```
systemctl disable wicked.service
systemctl --force enable NetworkManager.service
systemctl start network.service
```

Then check whether the currently selected service is actually NetworkManager:

```
systemctl -p network.service
```

And update /etc/resolv.conf:

```
netconfig update
```

Or reboot after the systemctl commands to restart also wpa\_supplicant.

### 1.3 Warning: No Location for Bootloader Stage1 Selected

During the initial installation, in the summary view of YaST, a warning as follows can appear below the bootloader section: “Warning: No location for bootloader stage1 selected. Unless you know what are you doing please select above location.”

This warning is a bug in YaST (now fixed in Factory) and you can safely ignore it.

### 1.4 Btrfs and Windows XP

If you have Windows XP and want to install openSUSE 13.2 with Btrfs, an error message in YaST will inform you about problems during the bootloader installation.

The safest option is to install in a partition with Ext4 instead of Btrfs. There is a fix that will reach Factory soon, but will be not present for 13.2.

### 1.5 Unbranded Grub2 on New Installs From Live

A bug in YaST prevents the branding in GRUB2 bootloader when installed from the LiveCD medium. Note, the preferred way to install openSUSE 13.2 is using the DVD or the NET install. Both mediums generate a proper branded bootloader during the installation.

## 1.6 NET Installation Using Wifi

Performing the NET install using Wifi presents some problems in YaST. Fixing this is work in progress and will be soon available. Meanwhile the only option is to use a wire connection to complete the NET installation.

## 2 ماع

### 2.1 UEFI—دت مملات باثل ا جمان ربل ا ده ج او

Prior to installing openSUSE on a system that boots using UEFI (Unified Extensible Firmware Interface), you are urgently advised to check for any firmware updates the hardware vendor recommends and, if available, to install such an update. A pre-installed Windows 8 is a strong indication that your system boots using UEFI.

Background: Some UEFI firmware has bugs that cause it to break if too much data gets written to the UEFI storage area. Nobody really knows how much "too much" is, though. openSUSE minimizes the risk by not writing more than the bare minimum required to boot the OS. The minimum means telling the UEFI firmware about the location of the openSUSE boot loader. Upstream Linux Kernel features that use the UEFI storage area for storing boot and crash information (pstore) have been disabled by default. Nevertheless, it is recommended to install any firmware updates the hardware vendor recommends.

### 2.2 UEFI، GPT، ماسق أو MS-DOS

Together with the EFI/UEFI specification, a new style of partitioning arrived: GPT (GUID Partition Table). This new schema uses globally unique identifiers (128-bit values displayed in 32 hexadecimal digits) to identify devices and partition types.

Additionally, the UEFI specification also allows legacy MBR (MS-DOS) partitions. The Linux boot loaders (ELILO or GRUB2) try to automatically generate a GUID for those legacy partitions, and write them to the firmware. Such a GUID can change frequently, causing a rewrite in the firmware. A rewrite consist of two different operation: removing the old entry and creating a new entry that replaces the first one.

نم قركاذل ا ررحتو ةفوذحمل تال اخدال ا عي مجتب هوقت ةشي دحل ا ةتبائل ا جمل بل ا  
ع مج ءانثأ ةتبائل ا جمل بل ا يف لل خ دوجو دن ع ةل كشم أشنت دق . ةمي دقل ا تال اخدال ا  
عالق ا لى ع ماظنل ا قردق مدع يف ببستى دق اذمو ؛ تال اخدال ا هذه ريرحتو  
امامت ةل كشم ا هذه يدافتل دي دج GPT لى ا مي دقل ا MBR مسق لى وحت : طيسب ل حل ا

### 2.3 نأل ا عالق ا عضو يف نوكت امدن ع عالق ا

نم أا ا عالق ا ني كمت دن ع UEFI عضو يف قزه أا لى ع طقف رثوي اذه

The new version of the shim loader allows more machines to boot with Secure Boot enabled than with openSUSE 13.1. Nevertheless, in case of trouble, first update the BIOS of your machine to the latest version. If the BIOS update does not help, report the model of your machine to the wiki (<http://en.opensuse.org/openSUSE:UEFI>). Then we can track it for the next release.

## 3 ماظنل ا ةي قرت

## 4 ينقت

### 4.1 عم تي بثل ا ةيل مم ءانثأ ةشاشل ا لى ع ةلمهل ا تاناي بل ا Nouveau ةق اوس

يول عل ا ءزل ا يف شي وشت تبثل ا رهظي دق ، NVIDIA تاقاطب عم ةمظنل ا لى ع ب يف  
هذه كتهج او اذ ا nouveau يضل ا لى غشتل ا جمل انرب عم لكشم ببسب ةشاشل ا نم  
م ث نمو تبثل ا لى غشتل a kernel nouveau ةي طمنل ا ةدحول ا لى طعت لكشمي ، ةل كشم ا  
ماظنل ا ةي قرت و ا تي بثل ا دعب ى رخ أ قرم ا ني كمت

ددح ، تي بثل ا طئاسو لى غشت درجمب ، kernel ةي طمنل ا ةدحول ا لى طعتل  
يذل ا رطسل ا لى ا بهذا م ث . تامل عمل ا ريرحتل 'e' رتخا م ث grub يف 'تي بثل ا رايخ  
ةي اهنل ا يف brokenmodules=nouveau ةفاضل م قو ('linux' or 'linuxefi') ةمل كب ءدبي

تي ببت دعب . قدي دجل ا تامل عمل ا عم عا ل ق ا ل ا عبات مل F10 حات فمل ا ل ع طغضا ن آل ا  
/etc/modprobe.d/50-nouveau ريرحتب ا ي طمنل ا ق دحول ا 'ن ي كمت ق د ا ع ل كن كمي . ماظنل ا  
blacklist.conf اهت فضا ي تلل ا ت ا ل ا خ د ا ل ا ق ل ز ا و .

## 4.2 Information About the FGLRX Driver

For more information about the AMD FGLRX drivers in openSUSE 13.2 and its status, see <https://lizards.opensuse.org/2014/11/01/fglrx-warning-opensuse-13-2-tumbleweed/>.

## 4.3 Second Static Mouse Pointer

If you see two mouse pointers and have two graphic boards, where one is an Intel board, try uninstalling `xf86-video-intel` and thus using the other one only. This will make disappear the static mouse pointer.

This and other issues with the Intel driver like (see [http://bugzilla.opensuse.org/show\\_bug.cgi?id=901506](http://bugzilla.opensuse.org/show_bug.cgi?id=901506)) will be worked on and, if possible, addressed with an online update.

## 4.4 Missing Dependencies for virt-manager

If you find a problem executing virt-manager, try installing `typelib-1_0-Gtk-3_0`, `typelib-1_0-SpiceClientGtk-3_0` and `typelib-1_0-GtkVnc-2_0`.

In the online update there will be a new version with those dependencies made explicit.

## 4.5 Modem Authorization After Suspend

openSUSE 13.2 is a more strict in security tha 13.1. If you are connected via a UMTS or 3G modem and you suspend the machine, the system will ask you for the root password before reconnecting.

You can change this behavior changing a line in `/etc/polkit-default-privs.standard`:

```
# ModemManager
org.freedesktop.ModemManager.Device.Control    auth_admin:auth_admin:yes
```

with:

```
# ModemManager
org.freedesktop.ModemManager.Device.Control    auth_admin_keep
```

## 4.6 Package Search Missing in GTK UI of YaST

The GTK interface of YaST does not feature a package search box. So if you are in GNOME or XFCE and you need this feature, use QT interface instead:

```
sudo /sbin/yast2 --qt
```

## 4.7 openSUSE pre-13.2 cifstab Migration

Mounting cifs shares at systems start via `/etc/samba/cifstab` has been discontinued and obsoleted. Now the generic `/etc/fstab` handles it.

The migration process requires two steps:

1. Append all your mount points from `/etc/samba/cifstab.rpmshave` to `/etc/fstab`.
2. Add `0 0` to the end of each new cifs mount line in `/etc/fstab`.

For more information and examples, see `/usr/share/doc/packages/cifs-utils/README.cifstab.migration` in the installed system.

## 4.8 Removing openSUSE 13.1 KDE Wallpaper After Upgrade

If the openSUSE 13.1 KDE Wallpaper still appears after the system upgrade, remove it from the user cache manually:

```
rm ~/.kde4/cache-*/plasma-wallpapers/usr/share/wallpapers/openSUSEdefault/contents/
images/*
```

## 4.9 MATE Desktop official integration

The MATE desktop is now officially available under openSUSE 13.2 with MATE version 1.8.1, the latest stable release. It provides an intuitive and attractive desktop environment using traditional metaphors for Linux and other Unix-like operating systems.

The objective, for openSUSE, is to provide the same experience users had when they used GNOME under openSUSE 11.4, with the main-menu and the Sonar theme.

## 4.10 Slow Start-up in GNOME

GNOME autologin can cause a slow boot process. Probably there is a race between services not correctly marked to depend on each other. Until the fix will be available as an online update, a workaround is to temporarily disable the GNOME autologin feature.

## 4.11 AppArmor and تانوذأل اتادادعإو

AppArmor is enabled by default. This means more security, but might prevent services from working if you run them in unexpected ways. If you encounter strange permission problems, try to switch the AppArmor profile for the affected service to complain mode with:

```
aa-complain /usr/bin/$your_service
```

ال يتل اءايشأل ليجستو ءءيش لئب حامسل اءن عى قرضتمل اءامدخال ىولش عضو  
اهب حمست



Even if it helps, report it as a bug! We want to fix AppArmor profiles to also cover corner cases.

## 5 تاعونم

### 5.1 YaST (Qt GUI): "Service Manager" Icon Appears Twice

In the System section of YaST (Qt GUI) the icon Service Manager appears twice. There is a bug in the Qt version of the YaST Control Center that does not honor the “hidden” flag in the desktop files.



This will get fixed with the next YaST online update.

## 6 تاقيل تلعل او تامول عمل انم ديزم

- ةطوغض مل صارقأل ىل عي دي هم تل اتافل مل ةءلق.
- مزحل انم قددحم ةعومجم لوح تلري ي غتل اب ةل ص فم تامول عم ىل لوصحلا

```
rpm --changelog -qp <FILENAME>.rpm
```

مزحل اس او <FILENAME>

- ينمزل ل جسلل يدي ف يدي نم ىل عل اى وتس مل ايف ريي غتل ل جس فل م نم ققحتلا ةثدحمل مزحل ىل عل امولج مت يتل تلري ي غتل ةفائل.
- يدي ف يدي عل ع قئاثو لي لدل ايف تامول عمل انم ديزم ىل عل روثعلا
- <https://activedoc.opensuse.org/>  ثي دحت وأ ةيفاض إقئاثو ىل ع يوتحي
- Visit <http://www.opensuse.org>  for the latest product news from openSUSE.

© 2014 SUSE LLC رشنل او عبطل اقو قح

Thanks for using openSUSE.

The openSUSE Team.